

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMOKHFDSTNC	NMO MOUNT, 17' RG-58A/U DUAL SHIELD, TNC	60%	US
Hutton	132-8	Larsen	SB24003	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 3' RG-174, NO CONN	60%	US
Hutton	132-8	Larsen	SB24006	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 6' RG-174, NO CONN	60%	US
Hutton	132-8	Larsen	SB80012	STEALTH BLADE, 806 - 896 MHz, 12' RG-174, NO CONN	60%	US
Hutton	132-8	Larsen	SB8003	STEALTH BLADE, 806 - 896 MHz, 3' RG-174, NO CONN	60%	US
Hutton	132-8	Larsen	NMO150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	KG3E1850UD	ON GLASS, ENCLOSED, 3 dB, 1850 - 1990 MHz, 14' UD	60%	US
Hutton	132-8	Larsen	KG3E1850UDMPL	ON GLASS, ENCLOSED, 3 dB, 1850 - 1990 MHz, 14' UD, MPL	60%	US
Hutton	132-8	Larsen	KG3E1850UDTNC	ON GLASS, ENCLOSED, 3 dB, 1850 - 1990 MHz, 14' UD, TNC	60%	US
Hutton	132-8	Larsen	GPS0007	WHITE ACTIVE GPS, 1575.4 MHz, SPECIFY COAX, LENGTH, NO CONN	60%	US
Hutton	132-8	Larsen	GPS0008	BLACK ACTIVE GPS, 1575.4 MHz, SPECIFY COAX, LENGTH, NO CONN	60%	US
Hutton	132-8	Larsen	GPSM01	SHRINK WRAP GPS MODULE, 1575.42 MHz, 5 dBic / 26 ± 2 dB LNA, 12' RG-174, MCX	60%	US
Hutton	132-8	Larsen	GPSM02	SHRINK WRAP GPS MODULE, 1575.42 MHz, 5 dBic / 26 ± 2 dB LNA, 12' RG-174, SMB	60%	US
Hutton	132-8	Larsen	GPSM03	SHRINK WRAP GPS MODULE, 1575.42 MHz, 5 dBic / 26 ± 2 dB LNA, 12' RG-174, SMA	60%	US
Hutton	132-8	Larsen	GPSM04	SHRINK WRAP GPS MODULE, 1575.42 MHz, 5 dBic / 26 ± 2 dB LNA, 12' RG-174, BNC	60%	US
Hutton	132-8	Larsen	GPS0001	WHITE ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, MCX	60%	US
Hutton	132-8	Larsen	GPS0002	BLACK ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, MCX	60%	US
Hutton	132-8	Larsen	GPS0003	WHITE ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	GPS0004	BLACK ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	GPS0005	WHITE ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, SMB	60%	US
Hutton	132-8	Larsen	GPS0006	BLACK ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, SMB	60%	US
Hutton	132-8	Larsen	GPS0009	WHITE ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, SMA M	60%	US
Hutton	132-8	Larsen	GPS0010	BLACK ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, SMA M	60%	US
Hutton	132-8	Larsen	GPS0011	WHITE ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, BNC	60%	US
Hutton	132-8	Larsen	GPS0012	BLACK ACTIVE GPS, 1575.4 MHz, 19.7' RG-174, BNC	60%	US
Hutton	132-8	Larsen	GPSDM01	WHITE GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, MCX	60%	US
Hutton	132-8	Larsen	GPSDM02	BLACK GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, MCX	60%	US
Hutton	132-8	Larsen	GPSDM03	WHITE GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	GPSDM04	BLACK GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	GPSDM05	WHITE GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, SMB	60%	US
Hutton	132-8	Larsen	GPSDM06	BLACK GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, SMB	60%	US
Hutton	132-8	Larsen	GPSDM07	WHITE GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, SMA	60%	US
Hutton	132-8	Larsen	GPSDM08	BLACK GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, SMA	60%	US
Hutton	132-8	Larsen	GPSDM09	WHITE GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, BNC	60%	US
Hutton	132-8	Larsen	GPSDM10	BLACK GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, BNC	60%	US
Hutton	132-8	Larsen	GPSGM01	GPS GLASS MOUNT, 1575.4 MHz, 17' RG-174, MCX	60%	US
Hutton	132-8	Larsen	GPSGM02	GPS GLASS MOUNT, 1575.4 MHz, 17' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	GPSGM03	GPS GLASS MOUNT, 1575.4 MHz, 17' RG-174, SMB	60%	US
Hutton	132-8	Larsen	GPSGM04	GPS GLASS MOUNT, 1575.4 MHz, 17' RG-174, SMA	60%	US
Hutton	132-8	Larsen	GPSGM05	GPS GLASS MOUNT, 1575.4 MHz, 17' RG-174, BNC	60%	US
Hutton	132-8	Larsen	GPSCW03	BASE ONLY, NO CONN	60%	US
Hutton	132-8	Larsen	GPSNMO01	WHITE GPS NMO, 1575.4 MHz	60%	US
Hutton	132-8	Larsen	GPSNMO02	BLACK GPS NMO, 1575.4 MHz	60%	US
Hutton	132-8	Larsen	GPSNMO11	WHITE GPS NMO WITH NMO MOUNT, 17' RG-58U/D, BNC	60%	US
Hutton	132-8	Larsen	GPSNMO12	BLACK GPS NMO WITH NMO MOUNT, 17' RG-58U/D, BNC	60%	US
Hutton	132-8	Larsen	GPSCW01	BASE, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW02	BASE, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSNMO09	WHITE GPS NMO WITH NMO MOUNT, 17' RG-58U/D, SMA	60%	US
Hutton	132-8	Larsen	GPSNMO10	BLACK GPS NMO WITH NMO MOUNT, 17' RG-58U/D, SMA	60%	US
Hutton	132-8	Larsen	GPSCW8001	BASE, 1/4 WAVE, 800 WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW8002	BASE, 1/4 WAVE, 800 WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSCW9001	BASE, 1/4 WAVE, 900 WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW9002	BASE, 1/4 WAVE, 900 WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSCW1501	BASE, 1/4 WAVE, VHF 150 WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW1502	BASE, 1/4 WAVE, VHF 150 WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSCW2201	BASE, 1/4 WAVE, VHF 220 WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW2202	BASE, 1/4 WAVE, VHF 220 WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSCW4501	BASE, 1/4 WAVE, UHF WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW4502	BASE, 1/4 WAVE, UHF WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSCW3E8001	BASE, 5dBi 800 WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW3E8002	BASE, 5dBi 800 WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSCW3E9001	BASE, 5dBi 900 WHIP, SMA/SMA	60%	US
Hutton	132-8	Larsen	GPSCW3E9002	BASE, 5dBi 900 WHIP, SMA/SMB	60%	US
Hutton	132-8	Larsen	GPSNMO03	WHITE GPS NMO WITH NMO MOUNT, 17' RG-58U/D, MCX	60%	US
Hutton	132-8	Larsen	GPSNMO04	BLACK GPS NMO WITH NMO MOUNT, 17' RG-58U/D, MCX	60%	US
Hutton	132-8	Larsen	GPSNMO05	WHITE GPS NMO WITH NMO MOUNT, 17' RG-58U/D, MMCX	60%	US
Hutton	132-8	Larsen	GPSNMO06	BLACK GPS NMO WITH NMO MOUNT, 17' RG-58U/D, MMCX	60%	US
Hutton	132-8	Larsen	GPSNMO07	WHITE GPS NMO WITH NMO MOUNT, 17' RG-58U/D, SMB	60%	US
Hutton	132-8	Larsen	GPSNMO08	BLACK GPS NMO WITH NMO MOUNT, 17' RG-58U/D, SMB	60%	US
Hutton	132-8	Larsen	NMOQW144	CHROME BASE / WHIP, UNITY, 144 - 148 MHz, ECONOMY 1/4 WAVE	60%	US
Hutton	132-8	Larsen	NMOQW152	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, ECONOMY 1/4 WAVE	60%	US
Hutton	132-8	Larsen	NMOQW406	CHROME BASE / WHIP, UNITY, 406 - 430 MHz, ECONOMY 1/4 WAVE	60%	US
Hutton	132-8	Larsen	NMOQW450	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, ECONOMY 1/4 WAVE	60%	US
Hutton	132-8	Larsen	NMOQW700	CHROME BASE / WHIP, 0 dB / 2 dBi, 740 - 806 MHz	60%	US
Hutton	132-8	Larsen	NMOQW700	CHROME BASE / WHIP, 0 dB / 2 dBi, 740 - 806 MHz	60%	US
Hutton	132-8	Larsen	NMOQW800	CHROME BASE / WHIP, UNITY, 806 - 896 MHz, ECONOMY 1/4 WAVE	60%	US
Hutton	132-8	Larsen	NMOQW900	CHROME BASE / WHIP, UNITY, 890 - 960 MHz, ECONOMY 1/4 WAVE	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	LABBLK	LA MOUNTING HARDWARE ONLY	60%	US
Hutton	132-8	Larsen	NMOKHFUDSMA	NMO MOUNT, 17' RG-58/U DUAL SHIELD, SMA	60%	US
Hutton	132-8	Larsen	LAKBLK	LA MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	LAWBQ	CHROME SPRING / WHIP, UNITY, 150 - 170 MHz, .125 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LMQK	CHROME Q BASE / WHIP, UNITY, 136 - 512 MHz, 17' CX, PL259, .070 CHROME WHIP	61%	US
Hutton	132-8	Larsen	KG220UDI/S	ON GLASS, I/S ONLY, 220 - 225 MHz, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LMC2/70B	Q LMC BASE / WHIP, UNITY, 144 - 148 / 442 - 448 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOKHFDSMA	NMO MOUNT, 17' RG-58/U DUAL SHIELD, SMA	60%	US
Hutton	132-8	Larsen	LAWBQB	BLACK SPRING / WHIP, UNITY, 150 - 170 MHz, .125 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	POKNOCONN	PO MOUNT, 17' CX, NO CONN	60%	US
Hutton	132-8	Larsen	KG1825	I/S GLASS MOUNT DIPOLE, UNITY, 806 - 896 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG1825	I/S GLASS MOUNT DIPOLE, UNITY, 806 - 896 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	LA150BCO	LA COIL, 3 dB, 144 - 174 MHz	60%	US
Hutton	132-8	Larsen	POK	PO MOUNT, 17' UD, MPL	61%	US
Hutton	132-8	Larsen	MS3E900SMA	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' RG-174, SMA	60%	US
Hutton	132-8	Larsen	MS3E900SMA	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' RG-174, SMA	60%	US
Hutton	132-8	Larsen	KGU825UD	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KGU825UD	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, NO CONN	61%	US
Hutton	132-8	Larsen	MSU150SMA	2" MAG MOUNT / WHIP, UNITY, 150 - 160 MHz, 12' RG-174, SMA	60%	US
Hutton	132-8	Larsen	LA150U	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA UNPLATED WHIP	60%	US
Hutton	132-8	Larsen	NMOQ2/70B	BASE / WHIP, UNITY, 144 - 148 / 440 - 450 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	KGU825UDFME	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, FME	61%	US
Hutton	132-8	Larsen	KGU825UDFME	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, FME	61%	US
Hutton	132-8	Larsen	KGU825UDMPL	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, MPL	61%	US
Hutton	132-8	Larsen	KGU825UDMPL	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, MPL	61%	US
Hutton	132-8	Larsen	KGU825UDTNC	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, TNC	61%	US
Hutton	132-8	Larsen	KGU825UDTNC	ON GLASS, UNITY, 806 - 896 MHz, 17' UD, TNC	61%	US
Hutton	132-8	Larsen	LA150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LA150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	KD4150/450	COMMERCIAL DUAL BAND KD ANTENNA	60%	US
Hutton	132-8	Larsen	KD42/70	AMATEUR DUAL BAND KD ANTENNA	63%	US
Hutton	132-8	Larsen	KG3E825UD	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD	61%	US
Hutton	132-8	Larsen	KG3E825UD	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD	61%	US
Hutton	132-8	Larsen	KG3E900UD	ON GLASS, ENCLOSED, 890 - 960 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG3E900UD	ON GLASS, ENCLOSED, 890 - 960 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG825UD	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	KG825UD	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	NMO2/70BCO	NMO COIL, 2.4 dB / 4 dB, 144 - 148 MHz	78%	US
Hutton	132-8	Larsen	NMO220HWBCO	HW NMO COIL, 2.5 dB, 220 - 225 MHz	60%	US
Hutton	132-8	Larsen	LA150B	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	KG3E825UDFME	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD, FME	61%	US
Hutton	132-8	Larsen	KG3E825UDFME	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD, FME	61%	US
Hutton	132-8	Larsen	KG3E825UDMPL	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD, MPL	61%	US
Hutton	132-8	Larsen	KG3E825UDMPL	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD, MPL	61%	US
Hutton	132-8	Larsen	KG3E825UDTNC	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD, TNC	61%	US
Hutton	132-8	Larsen	KG3E825UDTNC	ON GLASS, ENCLOSED, 3 dB, 806 - 896 MHz, 14' UD, TNC	61%	US
Hutton	132-8	Larsen	KG3E900UDFME	ON GLASS, ENCLOSED, 3 dB, 890 - 960 MHz, 14' UD, FME	61%	US
Hutton	132-8	Larsen	KG3E900UDFME	ON GLASS, ENCLOSED, 3 dB, 890 - 960 MHz, 14' UD, FME	61%	US
Hutton	132-8	Larsen	KG3E900UDMPL	ON GLASS, ENCLOSED, 3 dB, 890 - 960 MHz, 14' UD, MPL	61%	US
Hutton	132-8	Larsen	KG3E900UDMPL	ON GLASS, ENCLOSED, 3 dB, 890 - 960 MHz, 14' UD, MPL	61%	US
Hutton	132-8	Larsen	KG3E900UDTNC	ON GLASS, ENCLOSED, 3 dB, 890 - 960 MHz, 14' UD, TNC	61%	US
Hutton	132-8	Larsen	KG3E900UDTNC	ON GLASS, ENCLOSED, 3 dB, 890 - 960 MHz, 14' UD, TNC	61%	US
Hutton	132-8	Larsen	KG825UDFME	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, FME	60%	US
Hutton	132-8	Larsen	KG825UDFME	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, FME	60%	US
Hutton	132-8	Larsen	KG825UDMPL	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, MPL	60%	US
Hutton	132-8	Larsen	KG825UDMPL	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, MPL	60%	US
Hutton	132-8	Larsen	KG825UDTNC	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, TNC	60%	US
Hutton	132-8	Larsen	KG825UDTNC	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, TNC	60%	US
Hutton	132-8	Larsen	MHW150BCO	MHW COIL, 144 - 174 MHz	61%	US
Hutton	132-8	Larsen	GPS3VDM	GPS 3 VOLT DIRECT MOUNT, 5 dBic, 1575.42 MHz, 16.4' RG-174	60%	US
Hutton	132-8	Larsen	PHW150BCO	PHW COIL, 144 - 174 MHz	60%	US
Hutton	132-8	Larsen	NMO220CHW	HW COIL / WHIP, 2.5 dB, 220 - 225 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LA150UK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259 CONN, .100 UNPLATED WHIP	60%	US
Hutton	132-8	Larsen	MM2/70PL	3" MAG MOUNT / WHIP, UNITY, 144 - 148 / 442 - 448 MHz, 12' DS, PL259, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	MHW150C	COIL / WHIP, 2.5 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LA150CK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259 CONN, .100 CHROME WHIP	60%	US
Hutton	132-8	Larsen	LA150CK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259 CONN, .100 CHROME WHIP	60%	US
Hutton	132-8	Larsen	MHW406C	COIL / WHIP, 3.4 dB, 406 - 420 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	MHW450C	COIL / WHIP, 3.4 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	KGC/P3EUDFME	ON GLASS, 3 dB, 825 - 896 / 1850 - 1990 MHz, FME	60%	US
Hutton	132-8	Larsen	KGC/P3EUDFME	ON GLASS, 3 dB, 825 - 896 / 1850 - 1990 MHz, FME	60%	US
Hutton	132-8	Larsen	KGC/P3EUDMPL	ON GLASS, 3 dB, 825 - 896 / 1850 - 1990 MHz, MPL	60%	US
Hutton	132-8	Larsen	KGC/P3EUDMPL	ON GLASS, 3 dB, 825 - 896 / 1850 - 1990 MHz, MPL	60%	US
Hutton	132-8	Larsen	KGC/P3EUDTNC	ON GLASS, 3 dB, 825 - 896 / 1850 - 1990 MHz, TNC	60%	US
Hutton	132-8	Larsen	KGC/P3EUDTNC	ON GLASS, 3 dB, 825 - 896 / 1850 - 1990 MHz, TNC	60%	US
Hutton	132-8	Larsen	LA150BK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO2/70C	COIL/WHIP, 2.4 dB / 4 dB, 144 - 148 / 440 - 450 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	PHW150C	COIL / WHIP, 2.4 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMO2/70B	COIL / WHIP, 2.4 dB / 4 dB, 144 - 148 / 440 - 450 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	KG406UD	ON GLASS, 2 dBi, 406 - 420 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG420UD	ON GLASS, 2 dBi, 420 - 440 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG440UD	ON GLASS, 2 dBi, 440 - 460 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG450UD	ON GLASS, 2 dBi, 450 - 470 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG470UD	ON GLASS, 2 dBi, 470 - 490 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG490UD	ON GLASS, 2 dBi, 490 - 512 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG406UDPL	ON GLASS, 2 dBi, 406 - 420 MHz, 14' UD, PL259T	61%	US
Hutton	132-8	Larsen	KG420UDPL	ON GLASS, 2 dBi, 420 - 440 MHz, 14' UD, PL259T	61%	US
Hutton	132-8	Larsen	KG440UDPL	ON GLASS, 2 dBi, 440 - 460 MHz, 14' UD, PL259T	61%	US
Hutton	132-8	Larsen	KG450UDPL	ON GLASS, 2 dBi, 450 - 470 MHz, 14' UD, PL259T	61%	US
Hutton	132-8	Larsen	KG470UDPL	ON GLASS, 2 dBi, 470 - 490 MHz, 14' UD, PL259T	61%	US
Hutton	132-8	Larsen	LP800MPL	LOW PROFILE, UNITY, 806 - 960 MHz, 17' UD, MPL CRIMP	60%	US
Hutton	132-8	Larsen	LP800TNC	LOW PROFILE, UNITY, 806 - 960 MHz, 17' UD, TNC CRIMP	60%	US
Hutton	132-8	Larsen	LP800NMOUD	NMO LOW PROFILE, UNITY, 806 - 896 MHz, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LP800NMOUDW	WHITE NMO LOW PROFILE, UNITY, 806 - 896 MHz, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	NMO2/70CK	COIL/WHIP, 2.4 dB / 4 dB, 144 - 148 / 440 - 450 MHz, 17' CX, PL259 CONN, .100 CHR WHIP	60%	US
Hutton	132-8	Larsen	KG144UD	ON GLASS, 2 dBi, 144 - 160 MHz, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	KG160UD	ON GLASS, 2 dBi, 160 - 174 MHz, 14' UD, NO CONN	61%	US
Hutton	132-8	Larsen	KG220UD	ON GLASS, 2 dBi, 220 - 225 MHz, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	NMO2/70BK	COIL/WHIP, 2.4 dB / 4 dB, 150 - 154 / 450 - 460 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	63%	US
Hutton	132-8	Larsen	KG144UDPL	ON GLASS, 2 dBi, 144 - 160 MHz, 14' UD, PL259	63%	US
Hutton	132-8	Larsen	KG160UDPL	ON GLASS, 2 dBi, 160 - 174 MHz, 14' UD, PL259	61%	US
Hutton	132-8	Larsen	KG220UDPL	ON GLASS, 2 dBi, 220 - 225 MHz, 14' UD, PL259	60%	US
Hutton	132-8	Larsen	BSA118B	RADIAL BASE / WHIP, 3 dB, 118 - 121 MHz, MOUNT HARDWARE INCLUDED	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL1	ON GLASS, DISGUISE, UNITY, 130 - 139 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL2	ON GLASS, DISGUISE, UNITY, 130 - 139 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL3	ON GLASS, DISGUISE, UNITY, 140 - 149 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL4	ON GLASS, DISGUISE, UNITY, 140 - 149 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL5	ON GLASS, DISGUISE, UNITY, 150 - 159 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL6	ON GLASS, DISGUISE, UNITY, 150 - 159 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL7	ON GLASS, DISGUISE, UNITY, 160 - 170 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KGFFREQUDPL8	ON GLASS, DISGUISE, UNITY, 160 - 170 MHz, 14' UD, PL259 CONN	61%	US
Hutton	132-8	Larsen	KG2/70CXFME	ON GLASS, 2/4.2 dBi, 144 - 148 / 442 - 448 MHz, 14' CX, FME CRIMP	63%	US
Hutton	132-8	Larsen	KG2/70CXPL	ON GLASS, 2/4.2 dBi, 144 - 148 / 442 - 448 MHz, 14' CX, FME TO PL259	63%	US
Hutton	132-8	Larsen	PA18806N	PANEL, 8 dBi, 806 - 866 MHz, N CONN, SINGLE ELEMENT	60%	US
Hutton	132-8	Larsen	PA18824N	PANEL, 8 dBi, 824 - 896 MHz, N CONN, SINGLE ELEMENT	60%	US
Hutton	132-8	Larsen	PA2101850N	PANEL, 10 dBi, 1850 - 1990 MHz, N CONN, DUAL ELEMENT	60%	US
Hutton	132-8	Larsen	PA4142400N	PANEL, 14 dBi, 2400 - 2485 MHz, 3' UD, N CONN, QUAD ELEMENT	60%	US
Hutton	132-8	Larsen	NMOQW152CX10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' CX, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152CX10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' CX, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152UD10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' UD, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152UD10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' UD, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450CX10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' CX, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450CX10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' CX, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450UD10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' UD, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450UD10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' UD, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW800UD10	CHROME BASE / WHIP, UNITY, 806 - 896 MHz, 17' UD, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW800UD10	CHROME BASE / WHIP, UNITY, 806 - 896 MHz, 17' UD, HF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152CXFME10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' CX HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152CXFME10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' CX HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152UDFME10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' UD, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW152UDFME10	CHROME BASE / WHIP, UNITY, 152 - 162 MHz, 17' UD, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450CXFME10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' CX, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450CXFME10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' CX, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450UDFME10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' UD, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW450UDFME10	CHROME BASE / WHIP, UNITY, 450 - 470 MHz, 17' UD, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW800UDFME10	CHROME BASE / WHIP, UNITY, 806 - 896 MHz, 17' UD, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQW800UDFME10	CHROME BASE / WHIP, UNITY, 806 - 896 MHz, 17' UD, HF MOUNT, FME CRIMP INST, 10 PACK	60%	US
Hutton	132-8	Larsen	#10X32	SET SCREWS, 10-32 THREADS, 25/PKG	60%	US
Hutton	132-8	Larsen	#6X32	SET SCREWS, 6-32 THREADS, 25/PKG	60%	US
Hutton	132-8	Larsen	#8X32	SET SCREWS, 8-32 THREADS, 25/PKG	60%	US
Hutton	132-8	Larsen	58FCP	CONNECTOR, UHF FCP PLUG, RG-58	60%	US
Hutton	132-8	Larsen	A4	ADAPTER / BSA / BA / SO239 TO NMO MOUNT	60%	US
Hutton	132-8	Larsen	AC0056	CRIMP TOOL, RG-58 / RG-174, B8218 BNC	60%	US
Hutton	132-8	Larsen	AC0065	CASSETTE FOR COAX, STRIPPER / AC0059	60%	US
Hutton	132-8	Larsen	AC0102	N CONN (PL259 STYLE) FOR RG-58 / RG-8	60%	US
Hutton	132-8	Larsen	BA	BULKHEAD ADAPTER MOUNT HARDWARE	60%	US
Hutton	132-8	Larsen	BAHEXNUT	HEX, NUT FOR BULKHEAD ADAPTER	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	BALL1B	BLACK WHIP TIP W490 & W540, 10/PKG	60%	US
Hutton	132-8	Larsen	BALL2B	BLACK WHIP TIP Q, NMOQ, NLAQ/RND, 10/PKG	60%	US
Hutton	132-8	Larsen	BALL3B	BLACK WHIP TIP UHF GAIN ANT/RND, 10/PKG	60%	US
Hutton	132-8	Larsen	BALL4	ROD TIP WBQ800 ANTENNAS	60%	US
Hutton	132-8	Larsen	BANOHWARE	BULKHEAD ADAPTER, NO HARDWARE	60%	US
Hutton	132-8	Larsen	BATTBOLT	BATTERY BOLT WITH TERMINAL, 3/8" RING LEADS	60%	US
Hutton	132-8	Larsen	BNC	CONNECTOR / MALE SOLDER, RG-58	60%	US
Hutton	132-8	Larsen	BNC174	CONNECTOR, BNC CRIMP PLUG, RG-174/U	60%	US
Hutton	132-8	Larsen	BNCCBJ58	CONNECTOR, BNC CRIMP B JACK, RG-58/U	60%	US
Hutton	132-8	Larsen	BNCCJ58	CONNECTOR, BNC CRIMP JACK, RG-58/U	60%	US
Hutton	132-8	Larsen	BNCCRIMP	CONNECTOR, BNC CRIMP / MALE, RG-58	60%	US
Hutton	132-8	Larsen	BNCMMBNC	MAGNETIC MOUNT WITH BNC ON BOTH ENDS	60%	US
Hutton	132-8	Larsen	BNCMMTNC	BNC MAGNETIC MOUNT, TNC CRIMP, COAX	60%	US
Hutton	132-8	Larsen	BNCQ	BNC BASE / WHIP, UNITY, 136 - 512 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	BSA118KIT	BASE MOUNT KIT, 118 - 121 MHz, .070 DIA CHROME RADIALS @ 24"	60%	US
Hutton	132-8	Larsen	BSA132B	RADIAL BASE / WHIP, 3 dB, 131 - 135 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA150B	RADIAL BASE / WHIP, 3 dB, 144 - 174 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA150C	RADIAL BASE / WHIP, 3 dB, 144 - 174 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA220C	RADIAL BASE / WHIP, 3 dB, 200 - 225 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA406C	RADIAL BASE / WHIP, 3.4 dB, 406 - 420 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA440C	RADIAL BASE / WHIP, 3.4 dB, 440 - 460 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA450C	RADIAL BASE / WHIP, 3.4 dB, 450 - 470 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA45C	RADIAL BASE / WHIP, UNITY, 45 - 50 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA45KIT	GROUND PLANE KIT FOR BSA45C	60%	US
Hutton	132-8	Larsen	BSA470C	RADIAL BASE / WHIP, 3.4 dB, 470 - 490 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSA490C	RADIAL BASE / WHIP, 3.4 dB, 490 - 512 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSADC450	DC GROUNDED BS / WHIP, 4 dB, 490 - 512 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	BSAKIT	BASE MOUNT KIT, 144 - 512 MHz, .070 DIA CHROME RADIALS	60%	US
Hutton	132-8	Larsen	CM806B	BLACK CM ANTENNA, 3 dB, 806 - 866 MHz	60%	US
Hutton	132-8	Larsen	CM806BNMO	CM NMO BASE / WHIP, 3 dB, 806 - 866 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	CM825B	BLACK CM ANTENNA, 3 dB, 825 - 896 MHz	60%	US
Hutton	132-8	Larsen	CM825BNMO	CM NMO BASE / WHIP, 3 dB, 825 - 896 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	CX1000	1000' ROLL OF RG58A/U SINGLE SHIELD COAX	60%	US
Hutton	132-8	Larsen	CX1000	1000' ROLL OF RG58A/U SINGLE SHIELD COAX	60%	US
Hutton	132-8	Larsen	CXCOAX	CABLE CX/RG-58A/U, STRANDED CTR POLYETHYLENE DIELECTRIC	60%	US
Hutton	132-8	Larsen	CXCOAX	CABLE CX/RG-58A/U, STRANDED CTR POLYETHYLENE DIELECTRIC	60%	US
Hutton	132-8	Larsen	DS1000	1000' ROLL OF RG58A/U DUAL SHIELD COAX	60%	US
Hutton	132-8	Larsen	DS1000	1000' ROLL OF RG58A/U DUAL SHIELD COAX	60%	US
Hutton	132-8	Larsen	DSCOAX	CABLE DS/RG-58A/U, STRANDED CTR POLYETHYLENE DIELECTRIC	60%	US
Hutton	132-8	Larsen	DSCOAX	CABLE DS/RG-58A/U, STRANDED CTR POLYETHYLENE DIELECTRIC	60%	US
Hutton	132-8	Larsen	FB	ADAPTER, FME TO BNC MALE	60%	US
Hutton	132-8	Larsen	FB1136	RADIAL BASE / WHIP, 3.6 dB, 136 - 230 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2406	BASE STATION, 3 dB, 406 - 420 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2406WA	BASE / WHIP ONLY, 3 dB, 406 - 420 MHz	60%	US
Hutton	132-8	Larsen	FB2420	BASE STATION, 3 dB, 420 - 440 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2420WA	BASE / WHIP ONLY, 3 dB, 420 - 440 MHz	60%	US
Hutton	132-8	Larsen	FB2440	BASE STATION, 3 dB, 440 - 460 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2440WA	BASE / WHIP ONLY, 3 dB, 440 - 460 MHz	60%	US
Hutton	132-8	Larsen	FB2450	BASE STATION, 3 dB, 450 - 470 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2450WA	BASE / WHIP ONLY, 3 dB, 450 - 470 MHz	60%	US
Hutton	132-8	Larsen	FB2470	BASE STATION, 3 dB, 470 - 490 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2470WA	BASE / WHIP ONLY, 3 dB, 470 - 490 MHz	60%	US
Hutton	132-8	Larsen	FB2490	BASE STATION, 3 dB, 490 - 512 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB2490WA	BASE / WHIP ONLY, 3 dB, 490 - 512 MHz	60%	US
Hutton	132-8	Larsen	FB25	PKG OF 25 FME TO BNC MALE ADAPTER	60%	US
Hutton	132-8	Larsen	FB25	PKG OF 25 FME TO BNC MALE ADAPTER	60%	US
Hutton	132-8	Larsen	FB2BRACKET	MOUNT BRACKET / FB2 BASE	60%	US
Hutton	132-8	Larsen	FB35T800	BLADE BASE, 5 dB, 806 - 866 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB35T800WA	BLADE BASE / WHIP ONLY, 5 dB, 806 - 866 MHz	60%	US
Hutton	132-8	Larsen	FB35T825	BLADE BASE, 5 dB, 824 - 896 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB35T825WA	BLADE BASE / WHIP ONLY, 5 dB, 824 - 896 MHz	60%	US
Hutton	132-8	Larsen	FB35T900	BLADE BASE, 5 dB, 890 - 960 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB35T900WA	BLADE BASE / WHIP ONLY, 5 dB, 890 - 960 MHz	60%	US
Hutton	132-8	Larsen	FB3740	BASE / WHIP ONLY, 5 dB, 740 - 806 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB3740	BASE / WHIP ONLY, 5 dB, 740 - 806 MHz, MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB3740WA	BASE / WHIP ONLY, 5 dB, 740 - 806 MHz, NO MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB3740WA	BASE / WHIP ONLY, 5 dB, 740 - 806 MHz, NO MOUNT HARDWARE INCLUDED	60%	US
Hutton	132-8	Larsen	FB3800	BLADE BASE, 3 dB, 806 - 866 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB3800WA	BLADE BASE / WHIP ONLY, 3 dB, 806 - 866 MHz	60%	US
Hutton	132-8	Larsen	FB3825	BLADE BASE, 3 dB, 824 - 896 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB3825WA	BLADE BASE / WHIP ONLY, 3 dB, 824 - 896 MHz	60%	US
Hutton	132-8	Larsen	FB3900	BLADE BASE, 3 dB, 890 - 960 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB3900WA	BLADE BASE / WHIP ONLY, 3 dB, 890 - 960 MHz	60%	US
Hutton	132-8	Larsen	FB3BRACKET	MOUNT BRACKET / 5" ARM BLADE / ROUND BS BLADE AND ROUND SERIES	60%	US
Hutton	132-8	Larsen	FB45T2400	ROUND BASE, 5 dB, 2400 - 2485 MHz, 5" ARM MOUNT BRACKET INCLUDED	60%	US
Hutton	132-8	Larsen	FB45T2400WA	ROUND BASE / WHIP ONLY, 5 dB, 2400 - 2485 MHz	60%	US
Hutton	132-8	Larsen	FM	ADAPTER, FME TO MPL (MINI UHF)	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	FM25	ADAPTER, FME TO MPL (MINI UHF) - 25/PACK	60%	US
Hutton	132-8	Larsen	FMECJ174	CONNECTOR, FME CRIMP JACK, RG-174/U	60%	US
Hutton	132-8	Larsen	FMECP58	CONNECTOR, FME CRIMP PLUG, RG-58/U	60%	US
Hutton	132-8	Larsen	FMECRIMP	CONNECTOR, FME CRIMP / UNIV FEMALE, RG-58	60%	US
Hutton	132-8	Larsen	FMECRIMP25	CONNECTOR, FME CRIMP / UNIV FEMALE, RG-58, 25/PACK	60%	US
Hutton	132-8	Larsen	FN	ADAPTER, FME TO N MALE	60%	US
Hutton	132-8	Larsen	FN25	ADAPTER, FME TO N MALE, 25/PACK	60%	US
Hutton	132-8	Larsen	FP	ADAPTER, FME TO PL259	60%	US
Hutton	132-8	Larsen	FP25	ADAPTER, FME TO PL259, 25/PACK	60%	US
Hutton	132-8	Larsen	FSF	ADAPTER, FME TO SMA FEMALE	60%	US
Hutton	132-8	Larsen	FSM	ADAPTER, FME TO SMA MALE	60%	US
Hutton	132-8	Larsen	FSM25	ADAPTER, FME TO SMA MALE, 25/PACK	60%	US
Hutton	132-8	Larsen	FT	ADAPTER, FME TO TNC	60%	US
Hutton	132-8	Larsen	FT25	ADAPTER, FME TO TNC, 25/PACK	60%	US
Hutton	132-8	Larsen	GPS0015	WHITE GPS BASE STATION TIMING ANT, 1575.4 MHz, 37 dB, N FEMALE W/ MOUNT	60%	US
Hutton	132-8	Larsen	GPSCP00	GPS/CELL/PCS ROOF MOUNT, 824 - 894 / 1850 - 1990 / 1575.42 MHz, 16' RG-74/16' RG-174	60%	US
Hutton	132-8	Larsen	GPSCP00	GPS/CELL/PCS ROOF MOUNT, 824 - 894 / 1850 - 1990 / 1575.42 MHz, 16' RG-74/16' RG-174	60%	US
Hutton	132-8	Larsen	GPSCP00	GPS/CELL/PCS, 1574.5 - 1576.4 / 824 - 894 / 1850 - 1990 MHz, 14' RG-174, RG 58, NO CONN	60%	US
Hutton	132-8	Larsen	GPSCP00	GPS/CELL/PCS, 1574.5 - 1576.4 / 824 - 894 / 1850 - 1990 MHz, 14' RG-174, RG 58, NO CONN	60%	US
Hutton	132-8	Larsen	GPSCP00	GPS/CELL/PCS, 1574.5 - 1576.4 / 824 - 894 / 1850 - 1990 MHz, 14' RG-174, RG 58, NO CONN	60%	US
Hutton	132-8	Larsen	GPSCPGM00	GPS/CELL/PCS INT GLASS MNT, 824 - 894 / 1850 - 1990 / 1575.42 MHz, 16' RG-174, TNC/TNC/SMA	60%	US
Hutton	132-8	Larsen	GPSCPGM00	GPS/CELL/PCS INT GLASS MNT, 824 - 894 / 1850 - 1990 / 1575.42 MHz, 16' RG-174, TNC/TNC/SMA	60%	US
Hutton	132-8	Larsen	GPSCWCP00	GPS/CELL/PCS ROOF MOUNT, 824 - 894 / 1850 - 1990 / 1575.42 MHz, 16' RG-174, TNC/TNC/SMA	60%	US
Hutton	132-8	Larsen	GPSCWCP00	GPS/CELL/PCS ROOF MOUNT, 824 - 894 / 1850 - 1990 / 1575.42 MHz, 16' RG-174, TNC/TNC/SMA	60%	US
Hutton	132-8	Larsen	GPSU001	WHITE GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, MCX / FME	60%	US
Hutton	132-8	Larsen	GPSU002	BLACK GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, MCX / FME	60%	US
Hutton	132-8	Larsen	GPSU003	WHITE GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, MMCX / FME	60%	US
Hutton	132-8	Larsen	GPSU004	BLACK GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, MMCX / FME	60%	US
Hutton	132-8	Larsen	GPSU005	WHITE GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, SMB / FME	60%	US
Hutton	132-8	Larsen	GPSU006	BLACK GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, SMB / FME	60%	US
Hutton	132-8	Larsen	GPSU007	WHITE GPS/UHF, 1575.4 / 450 - 470 MHz, SPECIFY COAX, LENGTH, NO CONN	60%	US
Hutton	132-8	Larsen	GPSU008	BLACK GPS/UHF, 1575.4 / 450 - 470 MHz, SPECIFY COAX, LENGTH, NO CONN	60%	US
Hutton	132-8	Larsen	GPSU009	WHITE GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, SMA / FME	60%	US
Hutton	132-8	Larsen	GPSU010	BLACK GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, SMA / FME	60%	US
Hutton	132-8	Larsen	GPSU011	WHITE, GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, SMA / MPL	60%	US
Hutton	132-8	Larsen	GPSU011	WHITE, GPS/UHF, 1575.4 / 450 - 470 MHz, 19.7' RG-174 / RG-58U, SMA / MPL	60%	US
Hutton	132-8	Larsen	GROMMETS	PLASTIC GROMMETS, 3/4" HOLE MOUNT, 100/PKG	60%	US
Hutton	132-8	Larsen	GTCOUPLER	KG GLASS TEST COUPLER	60%	US
Hutton	132-8	Larsen	HP34	HOLE PLUGS FOR 3/4", 5/PKG	60%	US
Hutton	132-8	Larsen	HP38	HOLE PLUGS FOR 3/8", 6/PKG	60%	US
Hutton	132-8	Larsen	HS1	HOLE SAW FOR 3/4"	60%	US
Hutton	132-8	Larsen	HSBLADE	HOLE SAW BLADES, 2/PKG	60%	US
Hutton	132-8	Larsen	KD11FREQ	1/4 WAVE (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD12FREQ	1/4 WAVE (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD132MHW	COLLAPSIBLE 1/2 WAVE, 144 - 155 MHz	60%	US
Hutton	132-8	Larsen	KD13FREQ	1/4 WAVE (SPECIFY FREQUENCY 406 - 960 MHz)	60%	US
Hutton	132-8	Larsen	KD142MHW	COLLAPSIBLE 1/2 WAVE, 144 - 155 MHz	60%	US
Hutton	132-8	Larsen	KD14FREQ	1/4 WAVE (SPECIFY FREQUENCY 406 - 960 MHz)	60%	US
Hutton	132-8	Larsen	KD14FREQHW1	1/2 WAVE (SPECIFY FREQUENCY 315 - 409 MHz), BLACK CAP	60%	US
Hutton	132-8	Larsen	KD14FREQHW2	1/2 WAVE (SPECIFY FREQUENCY 416 - 504 MHz), BLACK CAP	60%	US
Hutton	132-8	Larsen	KD19FREQ	1/4 WAVE (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD1FREQHQ1	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD1FREQHQ2	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD1FREQHQ3	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD1FREQHQ4	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD1FREQHQ5	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD1FREQST	STOUT HELICAL (SPECIFY FREQUENCY 136 - 174 MHz)	60%	US
Hutton	132-8	Larsen	KD1UHF	UHF HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD22FREQHQ1	KD HQ/LM MOUNT (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD22FREQHQ2	KD HQ/LM MOUNT (SPECIFY FREQUENCY 142 - 149MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD22FREQHQ3	KD HQ/LM MOUNT (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD22FREQHQ4	KD HQ/LM MOUNT (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD22FREQHQ5	KD HQ/LM MOUNT (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD22UHF	UNITY, HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD22VHF1	UNITY, HELICAL (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD22VHF2	UNITY, HELICAL (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD22VHF3	UNITY, HELICAL (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD22VHF4	UNITY, HELICAL (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD22VHF5	UNITY, HELICAL (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD24UHF	UNITY, HELICAL (SPECIFY FREQUENCY 406 - 512 MHz),	60%	US
Hutton	132-8	Larsen	KD24VHF1	UNITY, HELICAL (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD24VHF2	UNITY, HELICAL (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD24VHF3	UNITY, HELICAL (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD24VHF4	UNITY, HELICAL (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD24VHF5	UNITY, HELICAL (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD2FREQHQ1	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	KD2FREQHQ2	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD2FREQHQ3	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD2FREQHQ4	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD2FREQHQ5	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD2FREQST	STOUT HELICAL (SPECIFY FREQUENCY 136 - 222 MHz)	60%	US
Hutton	132-8	Larsen	KD2UHF	UHF HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD2VHF1	VHF HELICAL, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD2VHF2	VHF HELICAL, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD2VHF3	VHF HELICAL, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD2VHF4	VHF HELICAL, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD2VHF5	VHF HELICAL, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD3FREQHQ1	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD3FREQHQ2	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD3FREQHQ3	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD3FREQHQ4	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD3FREQHQ5	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD3FREQST	STOUT HELICAL (SPECIFY FREQUENCY 136 - 174 MHz)	60%	US
Hutton	132-8	Larsen	KD3UHF	UHF HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD4150T	HELICAL VHF, 130 - 180 MHz	60%	US
Hutton	132-8	Larsen	KD4FREQHQ1	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD4FREQHQ2	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD4FREQHQ3	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD4FREQHQ4	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD4FREQHQ5	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD4FREQST	STOUT HELICAL (SPECIFY FREQUENCY 136 - 174 MHz)	60%	US
Hutton	132-8	Larsen	KD4UHF	UHF HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD4VHF1	VHF HELICAL, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD4VHF2	VHF HELICAL, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD4VHF3	VHF HELICAL, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD4VHF4	VHF HELICAL, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD4VHF5	VHF HELICAL, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD7FREQHQ1	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD7FREQHQ2	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD7FREQHQ3	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD7FREQHQ4	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD7FREQHQ5	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD7FREQST	STOUT HELICAL (SPECIFY FREQUENCY 136 - 174 MHz)	60%	US
Hutton	132-8	Larsen	KD7UHF	UHF HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD7VHF1	VHF HELICAL, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD7VHF2	VHF HELICAL, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD7VHF3	VHF HELICAL, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD7VHF4	VHF HELICAL, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD7VHF5	VHF HELICAL, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD9FREQHQ1	HELICAL 1/4 WAVE (SPECIFY FREQUENCY 136 - 222 MHz)	60%	US
Hutton	132-8	Larsen	KD9FREQHQ2	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD9FREQHQ3	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD9FREQHQ4	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD9FREQHQ5	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD9FREQST	HELICAL 1/4 WAVE, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KD9UHF	UHF HELICAL (SPECIFY FREQUENCY 406 - 512 MHz)	60%	US
Hutton	132-8	Larsen	KD9VHF1	VHF HELICAL, (SPECIFY FREQUENCY 136 - 140 MHz), BLUE CAP	60%	US
Hutton	132-8	Larsen	KD9VHF2	VHF HELICAL, (SPECIFY FREQUENCY 142 - 149 MHz), GREEN CAP	60%	US
Hutton	132-8	Larsen	KD9VHF3	VHF HELICAL, (SPECIFY FREQUENCY 150 - 161 MHz), YELLOW CAP	60%	US
Hutton	132-8	Larsen	KD9VHF4	VHF HELICAL, (SPECIFY FREQUENCY 162 - 174 MHz), RED CAP	60%	US
Hutton	132-8	Larsen	KD9VHF5	VHF HELICAL, (SPECIFY FREQUENCY 220 - 222 MHz), ORANGE CAP	60%	US
Hutton	132-8	Larsen	KG1440/S	ON GLASS, O/S ONLY, 2 dBi, 144 - 160 MHz	60%	US
Hutton	132-8	Larsen	KG1600/S	ON GLASS, O/S ONLY, 2 dBi, 160 - 174 MHz	60%	US
Hutton	132-8	Larsen	KG38250/S	ON GLASS, O/S ONLY, OPEN COIL, 3 dB, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	KG3E8250/S	ON GLASS, O/S ONLY, ENCLOSED, 3 dB, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	KG3E9000/S	ON GLASS, O/S ONLY, ENCLOSED, 3 dB, 890 - 960 MHz	60%	US
Hutton	132-8	Larsen	KG4060/S	ON GLASS, O/S ONLY, 2 dBi, 406 - 420 MHz	60%	US
Hutton	132-8	Larsen	KG4200/S	ON GLASS, O/S ONLY, 2 dBi, 420 - 440 MHz	60%	US
Hutton	132-8	Larsen	KG4400/S	ON GLASS, O/S ONLY, 2 dBi, 440 - 460 MHz	60%	US
Hutton	132-8	Larsen	KG4500DUD	ON GLASS, DISGUISE, UNITY, 450 - 470 MHz, 14' UD, PL259T	60%	US
Hutton	132-8	Larsen	KG4500/S	ON GLASS, O/S ONLY, 2 dBi, 450 - 470 MHz	60%	US
Hutton	132-8	Larsen	KG4700/S	ON GLASS, O/S ONLY, 2 dBi, 470 - 490 MHz	60%	US
Hutton	132-8	Larsen	KG4900/S	ON GLASS, O/S ONLY, 2 dBi, 490 - 512 MHz	60%	US
Hutton	132-8	Larsen	KG825UDI/S	ON GLASS, I/S ONLY, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	KGCP3EUD	ON GLASS, ENCLOSED, 3 dB / 3 dB, 824 / 1850 MHz, 15' UD, NO CONN	60%	US
Hutton	132-8	Larsen	KGCP3EUD	ON GLASS, ENCLOSED, 3 dB / 3 dB, 824 / 1850 MHz, 15' UD, NO CONN	60%	US
Hutton	132-8	Larsen	KGREINSTALL	ON GLASS, UNIVERSAL REINSTALL KIT	60%	US
Hutton	132-8	Larsen	KGREINSTALLDC	KG ON GLASS, DIE CUT REINSTALL KIT	60%	US
Hutton	132-8	Larsen	KGSWIVELMOUNT	KG SWIVEL MOUNT ASSEMBLY	60%	US
Hutton	132-8	Larsen	KGSWIVELMOUNT	KG SWIVEL MOUNT ASSEMBLY	60%	US
Hutton	132-8	Larsen	KGUHFUDI/S	ON GLASS, I/S ONLY, UHF, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	KGUHFUDI/S	ON GLASS, I/S ONLY, VHF, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LM150B	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM150BCO	LM COIL, 3 dB, 144 - 174 MHz	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	LM150BK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM150CK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM150CK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM150U	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA UNPLATED WHIP	60%	US
Hutton	132-8	Larsen	LM150UK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 UNPLATED WHIP	60%	US
Hutton	132-8	Larsen	LM220BCO	LM COIL, 3 dB, 220 - 225 MHz	60%	US
Hutton	132-8	Larsen	LM220C	COIL / WHIP, 3 dB, 220 - 225 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM220CK	COIL / WHIP, 3 dB, 220 - 225 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM3E800B	Q BASE / WHIP, ENCLOSED, 3 dB, 806 - 866 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	LM3E825B	Q BASE / WHIP, ENCLOSED, 3 dB, 824 - 896 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	LM3E900B	Q BASE / WHIP, ENCLOSED, 3 dB, 890 - 960 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	LM406B	BASE / WHIP, 3 dB, 406 - 420 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM406C	BASE / WHIP, 3.4 dB, 406 - 420 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM420B	BASE / WHIP, 3 dB, 420 - 440 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM420C	BASE / WHIP, 3.4 dB, 420 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM440B	BASE / WHIP, 3 dB, 440 - 460 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM440C	BASE / WHIP, 3.4 dB, 440 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM450B	BASE / WHIP, 3 dB, 450 - 470 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM450C	BASE / WHIP, 3.4 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM450CK	BASE / WHIP, 3.4 dB, 450 - 470 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM470B	BASE / WHIP, 3 dB, 470 - 490 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM470C	BASE / WHIP, 3.4 dB, 470 - 490 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM490B	BASE / WHIP, 3 dB, 490 - 512 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	LM490C	BASE / WHIP, 3.4 dB, 490 - 512 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM5T850B	Q BASE / WHIP, 5 dB, 824 - 896 MHz, .070 DIA TWIN OPEN COIL	60%	US
Hutton	132-8	Larsen	LM5T900B	Q BASE / WHIP, 5 dB, 890 - 960 MHz, .070 DIA TWIN OPEN COIL	60%	US
Hutton	132-8	Larsen	LM800	CHROME SPRING / WHIP, ENCLOSED, 4.5 dB, 806 - 866 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM825	CHROME SPRING / WHIP, ENCLOSED, 4.5 dB, 824 - 896 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LM900	CHROME SPRING / WHIP, ENC, 4.5 dB, 890 - 960 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	LMB	LM MOUNTING HARDWARE ONLY, 3/4" HOLE	60%	US
Hutton	132-8	Larsen	LMB1/4	LM MOUNTING HARDWARE ONLY, 1/4" LONGER STUD	60%	US
Hutton	132-8	Larsen	LMCAPB	RAIN CAP FOR LM MOUNT	60%	US
Hutton	132-8	Larsen	LMK	LM MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	LMKDS	LM MOUNT, 17' DS, NO CONN	60%	US
Hutton	132-8	Larsen	LMKDSFME	LM MOUNT, 17' DS, FME	60%	US
Hutton	132-8	Larsen	LMKDSMPL	LM MOUNT, 17' DS, MPL	60%	US
Hutton	132-8	Larsen	LMKDSN	LM MOUNT, 17' DS, N	60%	US
Hutton	132-8	Larsen	LMKDSTNC	LM MOUNT, 17' DS, TNC	60%	US
Hutton	132-8	Larsen	LMKFME	LM MOUNT, 17' CX, FME	60%	US
Hutton	132-8	Larsen	LMKMPL	LM MOUNT, 17' CX, MPL	60%	US
Hutton	132-8	Larsen	LMKN	LM MOUNT, 17' CX, N	60%	US
Hutton	132-8	Larsen	LMKNOCONN	LM MOUNT, 17' CX, NO CONN	60%	US
Hutton	132-8	Larsen	LMKTNC	LM MOUNT, 17' CX, TNC	60%	US
Hutton	132-8	Larsen	LMKUD	LM MOUNT, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LMKUDFME	LM MOUNT, 17' UD, FME	60%	US
Hutton	132-8	Larsen	LMKUDMPL	LM MOUNT, 17' UD, MPL	60%	US
Hutton	132-8	Larsen	LMKUDN	LM MOUNT, 17' UD, N	60%	US
Hutton	132-8	Larsen	LMKUDTNC	LM MOUNT, 17' UD, TNC	60%	US
Hutton	132-8	Larsen	LMMM	LM MAG MOUNT, 12' CX, UHF TYPE CONN	60%	US
Hutton	132-8	Larsen	LMMMBNC	LM MAG MOUNT, 12' CX, BNC	60%	US
Hutton	132-8	Larsen	LMMMDS	LM MAG MOUNT, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	LMMMDSFME	LM MAG MOUNT, 12' DS, FME	60%	US
Hutton	132-8	Larsen	LMMMDSMPL	LM MAG MOUNT, 12' DS, MPL	60%	US
Hutton	132-8	Larsen	LMMMDSN	LM MAG MOUNT, 12' DS, N	60%	US
Hutton	132-8	Larsen	LMMMDSPL	LM MAG MOUNT, 12' DS, PL259	60%	US
Hutton	132-8	Larsen	LMMMDFME	LM MAG MOUNT, 12' CX, FME	60%	US
Hutton	132-8	Larsen	LMMMPL	LM MAG MOUNT, 12' CX, MPL	60%	US
Hutton	132-8	Larsen	LMMMPL	LM MAG MOUNT, 12' CX, PL259	60%	US
Hutton	132-8	Larsen	LMMMR	LM 3.5" RND MAG MOUNT, 12' CX, UHF TYPE CONN	60%	US
Hutton	132-8	Larsen	LMMMRBNC	LM 3.5" RND MAG MOUNT, 12' CX, BNC	60%	US
Hutton	132-8	Larsen	LMMMRFME	LM 3.5" RND MAG MOUNT, 12' CX, FME	60%	US
Hutton	132-8	Larsen	LMMMRMPL	LM 3.5" RND MAG MOUNT, 12' CX, MPL	60%	US
Hutton	132-8	Larsen	LMMMRN	LM 3.5" RND MAG MOUNT, 12' CX, N	60%	US
Hutton	132-8	Larsen	LMMMRNOCONN	LM 3.5" RND MAG MOUNT, 12' CX, NO CONN	60%	US
Hutton	132-8	Larsen	LMMMRPL	LM 3.5" RND MAG MOUNT, 12' CX, PL259	60%	US
Hutton	132-8	Larsen	LMMMRRTNC	LM 3.5" RND MAG MOUNT, 12' CX, TNC	60%	US
Hutton	132-8	Larsen	LMMMTNC	LM MAG MOUNT, 12' CX, TNC	60%	US
Hutton	132-8	Larsen	LMTLP	LM TLP MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	LMTLPDS	LM TLP MOUNT, 17' DS, NO CONN	60%	US
Hutton	132-8	Larsen	LMTMB	CHROME LM TMB, 3/4", 17' CX, PL259	60%	US
Hutton	132-8	Larsen	LMUHFBASEB	LM BASE, 406 - 512 MHz	60%	US
Hutton	132-8	Larsen	LMWBQ	CHROME SPRING / WHIP, UNITY, 150 - 170 MHz, .125 DIA WHIP	60%	US
Hutton	132-8	Larsen	LMWBQB	SPRING / WHIP, UNITY, 150 - 170 MHz, .125 DIA WHIP	60%	US
Hutton	132-8	Larsen	LMWBQBK	SPRING / WHIP, UNITY, 150 - 170 MHz, 17' CX, PL259, .125 DIA WHIP	60%	US
Hutton	132-8	Larsen	LMWBQK	CHROME SPRING / WHIP, UNITY, 150 - 170 MHz, 17' CX, PL259, .125 DIA WHIP	60%	US
Hutton	132-8	Larsen	LP152NMO	BLACK NMO LOW PROFILE, UNITY, 151.02 - 152.98 MHz	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	LP152NMOW	WHITE NMO LOW PROFILE, UNITY, 151.02 - 152.98 MHz	60%	US
Hutton	132-8	Larsen	LP154NMO	BLACK NMO LOW PROFILE, UNITY, 152.96 - 155.04 MHz	60%	US
Hutton	132-8	Larsen	LP154NMOW	WHITE NMO LOW PROFILE, UNITY, 152.96 - 155.04 MHz	60%	US
Hutton	132-8	Larsen	LP156NMO	BLACK NMO LOW PROFILE, UNITY, 154.42 - 156.58 MHz	60%	US
Hutton	132-8	Larsen	LP156NMOW	WHITE NMO LOW PROFILE, UNITY, 154.42 - 156.58 MHz	60%	US
Hutton	132-8	Larsen	LP158NMO	BLACK NMO LOW PROFILE, UNITY, 156.38 - 158.62 MHz	60%	US
Hutton	132-8	Larsen	LP158NMOW	WHITE NMO LOW PROFILE, UNITY, 156.38 - 158.62 MHz	60%	US
Hutton	132-8	Larsen	LP160NMO	BLACK NMO LOW PROFILE, UNITY, 158.33 - 160.67 MHz	60%	US
Hutton	132-8	Larsen	LP160NMOW	WHITE NMO LOW PROFILE, UNITY, 158.33 - 160.67 MHz	60%	US
Hutton	132-8	Larsen	LP162NMO	BLACK NMO LOW PROFILE, UNITY, 160.29 - 162.71 MHz	60%	US
Hutton	132-8	Larsen	LP162NMOW	WHITE NMO LOW PROFILE, UNITY, 160.29 - 162.71 MHz	60%	US
Hutton	132-8	Larsen	LP164NMO	BLACK NMO LOW PROFILE, UNITY, 162.75 - 165.25 MHz	60%	US
Hutton	132-8	Larsen	LP164NMOW	WHITE NMO LOW PROFILE, UNITY, 162.75 - 165.25 MHz	60%	US
Hutton	132-8	Larsen	LP167NMO	BLACK NMO LOW PROFILE, UNITY, 165.21 - 167 - 79 MHz	60%	US
Hutton	132-8	Larsen	LP167NMOW	WHITE NMO LOW PROFILE, UNITY, 165.21 - 167 - 79 MHz	60%	US
Hutton	132-8	Larsen	LP169NMO	BLACK NMO LOW PROFILE, UNITY, 167.68 - 170.32 MHz	60%	US
Hutton	132-8	Larsen	LP169NMOW	WHITE NMO LOW PROFILE, UNITY, 167.68 - 170.32 MHz	60%	US
Hutton	132-8	Larsen	LP171NMO	BLACK NMO LOW PROFILE, UNITY, 170.16 - 172.84 MHz	60%	US
Hutton	132-8	Larsen	LP171NMOW	WHITE NMO LOW PROFILE, UNITY, 170.16 - 172.84 MHz	60%	US
Hutton	132-8	Larsen	LP174NMO	BLACK NMO LOW PROFILE, UNITY, 172.14 - 174.86 MHz	60%	US
Hutton	132-8	Larsen	LP174NMOW	WHITE NMO LOW PROFILE, UNITY, 172.14 - 174.86 MHz	60%	US
Hutton	132-8	Larsen	LP406NMO	NMO LOW PROFILE, UNITY, 406 - 420 MHz	60%	US
Hutton	132-8	Larsen	LP406NMOW	WHITE NMO LOW PROFILE, UNITY, 406 - 420 MHz	60%	US
Hutton	132-8	Larsen	LP420NMO	NMO LOW PROFILE, UNITY, 420 - 440 MHz	60%	US
Hutton	132-8	Larsen	LP420NMOW	WHITE NMO LOW PROFILE, UNITY, 420 - 440 MHz	60%	US
Hutton	132-8	Larsen	LP430NMO	LOW PROFILE, UNITY, 430 - 450 MHz, NMO MOUNTED	60%	US
Hutton	132-8	Larsen	LP430NMOW	WHITE LOW PROFILE, UNITY, 430 - 450 MHz, NMO MOUNTED	60%	US
Hutton	132-8	Larsen	LP450	LOW PROFILE, UNITY, 450 - 470 MHz, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LP450NMO	NMO LOW PROFILE, UNITY, 450 - 470 MHz	60%	US
Hutton	132-8	Larsen	LP450NMOW	WHITE NMO LOW PROFILE, UNITY, 450 - 470 MHz	60%	US
Hutton	132-8	Larsen	LP450W	WHITE LOW PROFILE, UNITY, 450 - 470 MHz, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LP470NMO	NMO LOW PROFILE, UNITY, 470 - 490 MHz	60%	US
Hutton	132-8	Larsen	LP470NMOW	WHITE NMO LOW PROFILE, UNITY, 470 - 490 MHz	60%	US
Hutton	132-8	Larsen	LP490NMO	NMO LOW PROFILE, UNITY, 490 - 512 MHz	60%	US
Hutton	132-8	Larsen	LP490NMOW	WHITE NMO LOW PROFILE, UNITY, 490 - 512 MHz	60%	US
Hutton	132-8	Larsen	LP800	LOW PROFILE, UNITY, 806 - 960 MHz, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LP800NMO	NMO LOW PROFILE, UNITY, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	LP800NMOW	WHITE NMO LOW PROFILE, UNITY, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	LP800W	WHITE LOW PROFILE, UNITY, 806 - 960 MHz, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	LPT2400NMOHF	BLACK NMO TRANSIT ANTENNA, 2 dBi, 2400 - 2500 MHz	60%	US
Hutton	132-8	Larsen	LPT2400NMOHFW	WHITE NMO TRANSIT ANTENNA, 2 dBi, 2400 - 2500 MHz	60%	US
Hutton	132-8	Larsen	LPT2400NMOHFW	WHITE NMO TRANSIT ANTENNA, 2 dBi, 2400 - 2500 MHz	60%	US
Hutton	132-8	Larsen	LPT406NMO	NMO TRANSIT ANTENNA, UNITY, 406 - 420 MHz	60%	US
Hutton	132-8	Larsen	LPT406NMOW	WHITE NMO TRANSIT ANTENNA, UNITY, 406 - 420 MHz	60%	US
Hutton	132-8	Larsen	LPT415NMO	TRANSIT COIL, UNITY, 415 - 430 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	LPT415NMOW	WHITE TRANSIT COIL, UNITY, 415 - 430 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	LPT430NMO	TRANSIT COIL, UNITY, 430 - 445 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	LPT430NMOW	WHITE TRANSIT COIL, UNITY, 430 - 445 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	LPT435NMO	TRANSIT COIL, UNITY, 435 - 450 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	LPT435NMOW	WHITE TRANSIT COIL, UNITY, 435 - 450 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	LPT450NMO	NMO TRANSIT ANTENNA, UNITY, 450 - 470 MHz	60%	US
Hutton	132-8	Larsen	LPT450NMOW	WHITE NMO TRANSIT ANTENNA, UNITY, 450 - 470 MHz	60%	US
Hutton	132-8	Larsen	LPT470NMO	NMO TRANSIT ANTENNA, UNITY, 470 - 490 MHz	60%	US
Hutton	132-8	Larsen	LPT470NMOW	WHITE NMO TRANSIT ANTENNA, UNITY, 470 - 490 MHz	60%	US
Hutton	132-8	Larsen	LPT490NMO	NMO TRANSIT ANTENNA, UNITY, 490 - 512 MHz	60%	US
Hutton	132-8	Larsen	LPT490NMOW	WHITE NMO TRANSIT ANTENNA, UNITY, 490 - 512 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800	TRANSIT ANTENNA, UNITY, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800	TRANSIT ANTENNA, UNITY, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800NMO	BLACK NMO TRANSIT ANTENNA, 2 dBi, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800NMO	BLACK NMO TRANSIT ANTENNA, 2 dBi, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800NMOW	WHITE NMO TRANSIT ANTENNA, 2 dBi, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800NMOW	WHITE NMO TRANSIT ANTENNA, 2 dBi, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT700/800W	WHITE TRANSIT ANTENNA, UNITY, 740 - 866 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900	TRANSIT ANTENNA, UNITY, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900	TRANSIT ANTENNA, UNITY, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900NMO	BLACK NMO TRANSIT ANTENNA, 2 dBi, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900NMO	BLACK NMO TRANSIT ANTENNA, 2 dBi, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900NMOW	WHITE NMO TRANSIT ANTENNA, 2 dBi, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900NMOW	WHITE NMO TRANSIT ANTENNA, 2 dBi, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900W	WHITE TRANSIT ANTENNA, UNITY, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT800/900W	WHITE TRANSIT ANTENNA, UNITY, 806 - 960 MHz	60%	US
Hutton	132-8	Larsen	LPT825/19NMOHF	BLACK DUAL BAND CELL/PCS NMO TRANSIT ANTENNA, 3 dBi / 4 dBi, 824 - 960 MHz / 1710 - 1990	60%	US
Hutton	132-8	Larsen	LPT825/19NMOHF	BLACK DUAL BAND CELL/PCS NMO TRANSIT ANTENNA, 3 dBi / 4 dBi, 824 - 960 MHz / 1710 - 1990	60%	US
Hutton	132-8	Larsen	LPT825/19NMOHFW	WHITE DUAL BAND CELL/PCS NMO TRANSIT ANTENNA, 3 dBi / 4 dBi, 824 - 960 MHz / 1710 - 1990	60%	US
Hutton	132-8	Larsen	LPT825/19NMOHFW	WHITE DUAL BAND CELL/PCS NMO TRANSIT ANTENNA, 3 dBi / 4 dBi, 824 - 960 MHz / 1710 - 1990	60%	US
Hutton	132-8	Larsen	MB38	CHROME MIRROR BRACKET, 3/8" HOLE	60%	US

Hutton Communications, Inc.  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	MM34	MAG MOUNT HOUSING WITH 3/4" HOLE	60%	US
Hutton	132-8	Larsen	MM3E800FME	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' DS, FME	60%	US
Hutton	132-8	Larsen	MM3E800FME	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' DS, FME	60%	US
Hutton	132-8	Larsen	MM3E800MPL	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' DS, MPL	60%	US
Hutton	132-8	Larsen	MM3E800MPL	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' DS, MPL	60%	US
Hutton	132-8	Larsen	MM3E800TNC	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' DS, TNC	60%	US
Hutton	132-8	Larsen	MM3E800TNC	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' DS, TNC	60%	US
Hutton	132-8	Larsen	MM3E900FME	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, FME CRIMP	60%	US
Hutton	132-8	Larsen	MM3E900FME	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, FME CRIMP	60%	US
Hutton	132-8	Larsen	MM3E900MPL	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, MPL CRIMP	60%	US
Hutton	132-8	Larsen	MM3E900MPL	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, MPL CRIMP	60%	US
Hutton	132-8	Larsen	MM3E900TNC	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, TNC CRIMP	60%	US
Hutton	132-8	Larsen	MM3E900TNC	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, TNC CRIMP	60%	US
Hutton	132-8	Larsen	MMBK	FOIL & TEFLON TAPE FOR SQUARE MAG MOUNTS	60%	US
Hutton	132-8	Larsen	MMC/P3EFME	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 825 - 896 / 1850 - 1990 MHz, FME	60%	US
Hutton	132-8	Larsen	MMC/P3EFME	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 825 - 896 / 1850 - 1990 MHz, FME	60%	US
Hutton	132-8	Larsen	MMC/P3EMPL	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 825 - 896 / 1850 - 1990 MHz, MPL	60%	US
Hutton	132-8	Larsen	MMC/P3EMPL	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 825 - 896 / 1850 - 1990 MHz, MPL	60%	US
Hutton	132-8	Larsen	MMC/P3ETNC	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 825 - 896 / 1850 - 1990 MHz, TNC	60%	US
Hutton	132-8	Larsen	MMC/P3ETNC	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 825 - 896 / 1850 - 1990 MHz, TNC	60%	US
Hutton	132-8	Larsen	MMU150DSD	3" MAG MOUNT / WHIP DISGUISE ANTENNA, UNITY, 150 - 155 MHz, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	MMU155DSD	3" MAG MOUNT / WHIP DISGUISE ANTENNA, UNITY, 155 - 160 MHz, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	MMU160DSD	3" MAG MOUNT / WHIP DISGUISE ANTENNA, UNITY, 160 - 165 MHz, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	MMU165DSD	3" MAG MOUNT / WHIP DISGUISE ANTENNA, UNITY, 165 - 170 MHz, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	MMU170DSD	3" MAG MOUNT / WHIP DISGUISE ANTENNA, UNITY, 170 - 175 MHz, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	MPLCJ174	CONNECTOR, MINI UHF, CRIMP JACK, 174/U	60%	US
Hutton	132-8	Larsen	MPLCJ58	CONNECTOR, MINI UHF, CRIMP JACK, 58/U	60%	US
Hutton	132-8	Larsen	MPLCP	CONNECTOR, MINI UHF, CRIMP PLUG, 174/U	60%	US
Hutton	132-8	Larsen	MPLCRIMP	CONNECTOR, MPL CRIMP / MINI UHF, RG-58	60%	US
Hutton	132-8	Larsen	MPLCRIMP25	PKG OF 25 MINI UHF CONNECTORS / MALE, RG-58	60%	US
Hutton	132-8	Larsen	MS3E2400SMA	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 2400 - 2485 MHz, 12' RG-58, SMA	60%	US
Hutton	132-8	Larsen	MS3E2400TNC	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 2400 - 2485 MHz, 12' RG-58, TNC	60%	US
Hutton	132-8	Larsen	MS3E800FME	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MS3E800FME	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MS3E800MPL	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	MS3E800MPL	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	MS3E800TNC	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, TNC	60%	US
Hutton	132-8	Larsen	MS3E800TNC	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, TNC	60%	US
Hutton	132-8	Larsen	MS3E900MPL	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	MS3E900MPL	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	MS3E900TNC	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' RG-174, TNC	60%	US
Hutton	132-8	Larsen	MS3E900TNC	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' RG-174, TNC	60%	US
Hutton	132-8	Larsen	MSC/P3UFME	2" MAG MOUNT, UNITY, 3 dB, 825 - 896 / 1850 - 1990 MHz, FME	60%	US
Hutton	132-8	Larsen	MSC/P3UFME	2" MAG MOUNT, UNITY, 3 dB, 825 - 896 / 1850 - 1990 MHz, FME	60%	US
Hutton	132-8	Larsen	MSC/P3UMPL	2" MAG MOUNT, UNITY, 3 dB, 825 - 896 / 1850 - 1990 MHz, MPL	60%	US
Hutton	132-8	Larsen	MSC/P3UMPL	2" MAG MOUNT, UNITY, 3 dB, 825 - 896 / 1850 - 1990 MHz, MPL	60%	US
Hutton	132-8	Larsen	MSC/P3UTNC	2" MAG MOUNT, UNITY, 3 dB, 825 - 896 / 1850 - 1990 MHz, TNC	60%	US
Hutton	132-8	Larsen	MSC/P3UTNC	2" MAG MOUNT, UNITY, 3 dB, 825 - 896 / 1850 - 1990 MHz, TNC	60%	US
Hutton	132-8	Larsen	MSTFME	2" MAG MOUNT / WHIP, UNITY, 144 - 965 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU144BNC	2" MAG MOUNT / WHIP, UNITY, 144 - 148 MHz, 12' RG-174, BNC	60%	US
Hutton	132-8	Larsen	MSU144FME	2" MAG MOUNT / WHIP, UNITY, 144 - 148 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU150FME	2" MAG MOUNT / WHIP, UNITY, 150 - 160 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU150MPL	2" MAG MOUNT / WHIP, UNITY, 150 - 160 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	MSU406FME	2" MAG MOUNT / WHIP, UNITY, 406 - 420 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU420FME	2" MAG MOUNT / WHIP, UNITY, 420 - 440 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU450FME	2" MAG MOUNT / WHIP, UNITY, 450 - 470 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU470FME	2" MAG MOUNT / WHIP, UNITY, 470 - 490 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU490FME	2" MAG MOUNT / WHIP, UNITY, 490 - 512 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU800FME	2" MAG MOUNT / WHIP, UNITY, 806 - 896 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	MSU800MPL	2" MAG MOUNT / WHIP, UNITY, 806 - 896 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	MSU800TNC	2" MAG MOUNT / WHIP, UNITY, 806 - 896 MHz, 12' RG-174, TNC	60%	US
Hutton	132-8	Larsen	MSU900FME	2" MAG MOUNT / WHIP, UNITY, 890 - 960 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	N	CONNECTOR, N MALE SOLDER, RG-58	60%	US
Hutton	132-8	Larsen	N8	CONNECTOR, MALE SOLDER, RG-8	60%	US
Hutton	132-8	Larsen	NCBJ58	CONNECTOR, N CRIMP B JACK, RG-58/U	60%	US
Hutton	132-8	Larsen	NCJ58	CONNECTOR, N CRIMP JACK, RG-58/U	60%	US
Hutton	132-8	Larsen	NCP8	CONNECTOR, N CRIMP PLUG, RG-B7618/U	60%	US
Hutton	132-8	Larsen	NCRIMP	CONNECTOR, N CRIMP MALE, RG-58	60%	US
Hutton	132-8	Larsen	NCRIMP25	PKG OF 25 N CRIMP CONNECTOR, MALE, RG-58	60%	US
Hutton	132-8	Larsen	NMO150/450/800	TRI-BAND, 2.14 dBi, 150 - 165, 450 - 470, 806 - 940 MHz, NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMO150/450BCO	NMO COIL, 1.6 dB / 3.8 dB, 150 - 154 MHz	60%	US
Hutton	132-8	Larsen	NMO150/450C	COIL/WHIP, 1.6 dB / 3.8 dB, 150 - 154 / 450 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO150/450CK	COIL/WHIP, 1.6 dB / 3.8 dB, 150 - 154 / 450 - 460 MHz, 17' CX, PL259, .100 DIA CHR WHIP	60%	US
Hutton	132-8	Larsen	NMO150B	COIL/WHIP, 3 dB, 144 - 174 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO150B	COIL/WHIP, 3 dB, 144 - 174 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO150BCO	NMO COIL, 3 dB, 144 - 174 MHz	60%	US
Hutton	132-8	Larsen	NMO150BCO	NMO COIL, 3 dB, 144 - 174 MHz	60%	US
Hutton	132-8	Larsen	NMO150BHW	HW COIL / WHIP, 2.5 dB, 144 - 174 MHz, .100 DIA BLACK WHIP	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMO150BK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO150BK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO150CHW	HW COIL / WHIP, 2.5 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO150CHW	HW COIL / WHIP, 2.5 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO150CK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO150CK	COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO150CK10	PKG OF 10, COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMO150CK10	PKG OF 10, COIL / WHIP, 3 dB, 144 - 174 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMO150HWBCO	HW NMO COIL, 2.5 dB, 144 - 174 MHz	60%	US
Hutton	132-8	Larsen	NMO150U	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA UNPLATED WHIP	60%	US
Hutton	132-8	Larsen	NMO150U	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA UNPLATED WHIP	60%	US
Hutton	132-8	Larsen	NMO2/70SH	SPG BASE/WHIP ENCLOSED, UNITY, 144 - 148 / 440 - 450 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO270B	COIL / WHIP, 3 dB, 220 - 225 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO220BCO	NMO COIL, 3 dB, 220 - 225 MHz	60%	US
Hutton	132-8	Larsen	NMO220BK	COIL / WHIP, 3 dB, 220 - 225 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO220C	COIL / WHIP, 3 dB, 220 - 225 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO220CK	COIL / WHIP, 3 dB, 220 - 225 MHz, 17' CX, PL259, .100 CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO27B	COIL / WHIP, UNITY, 27 - 31 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO27B	COIL / WHIP, UNITY, 27 - 31 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO27BCO	NMO COIL, UNITY, 27 - 31 MHz	60%	US
Hutton	132-8	Larsen	NMO27BCO	NMO COIL, UNITY, 27 - 31 MHz	60%	US
Hutton	132-8	Larsen	NMO27BK	COIL / WHIP, UNITY, 27 - 31 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO27BK	COIL / WHIP, UNITY, 27 - 31 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO27C	COIL / WHIP, UNITY, 27 - 31 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO27C	COIL / WHIP, UNITY, 27 - 31 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO27CK	COIL / WHIP, UNITY, 27 - 31 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO27CK	COIL / WHIP, UNITY, 27 - 31 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO27CK10	PKG OF 10, COIL / WHIP, UNITY, 27 - 31 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMO27CK10	PKG OF 10, COIL / WHIP, UNITY, 27 - 31 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMO30B	COIL / WHIP, UNITY, 30 - 35 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO30B	COIL / WHIP, UNITY, 30 - 35 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO30BCO	NMO COIL, UNITY, 30 - 35 MHz	60%	US
Hutton	132-8	Larsen	NMO30BCO	NMO COIL, UNITY, 30 - 35 MHz	60%	US
Hutton	132-8	Larsen	NMO30BK	COIL / WHIP, UNITY, 30 - 35 MHz, 17' CX, PL259 CONN, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO30BK	COIL / WHIP, UNITY, 30 - 35 MHz, 17' CX, PL259 CONN, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO30C	COIL / WHIP, UNITY, 30 - 35 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO30C	COIL / WHIP, UNITY, 30 - 35 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO30CK	COIL / WHIP, UNITY, 30 - 35 MHz, 17' CX, PL259, .100 CHROME	60%	US
Hutton	132-8	Larsen	NMO30CK	COIL / WHIP, UNITY, 30 - 35 MHz, 17' CX, PL259, .100 CHROME	60%	US
Hutton	132-8	Larsen	NMO34B	COIL / WHIP, UNITY, 34 - 40 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO34B	COIL / WHIP, UNITY, 34 - 40 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO34BCO	NMO COIL, UNITY, 34 - 40 MHz	60%	US
Hutton	132-8	Larsen	NMO34BCO	NMO COIL, UNITY, 34 - 40 MHz	60%	US
Hutton	132-8	Larsen	NMO34BK	COIL / WHIP, UNITY, 34 - 40 MHz, 17' CX, PL259, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO34BK	COIL / WHIP, UNITY, 34 - 40 MHz, 17' CX, PL259, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO34C	COIL / WHIP, UNITY, 34 - 40 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO34C	COIL / WHIP, UNITY, 34 - 40 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO34CK	COIL / WHIP, UNITY, 34 - 40 MHz, 17' CX, PL259, .100 CHROME	60%	US
Hutton	132-8	Larsen	NMO34CK	COIL / WHIP, UNITY, 34 - 40 MHz, 17' CX, PL259, .100 CHROME	60%	US
Hutton	132-8	Larsen	NMO3E700B	BASE / WHIP ENCLOSED, 3 dB / 5.2 dBi, 740 - 806 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO3E700B	BASE / WHIP ENCLOSED, 3 dB / 5.2 dBi, 740 - 806 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO3E800B	BASE / WHIP ENCLOSED, 3 dB, 806 - 866 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO3E800BMPL	BASE / WHIP ENCLOSED, 3 dB, 806 - 866 MHz, .073 DIA WHIP, 17' UD MPL	60%	US
Hutton	132-8	Larsen	NMO3E800BTNC	BASE / WHIP, 3 dB, 806 - 866 MHz, 17' UD, TNC, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO3E825B	BASE / WHIP ENCLOSED, 3 dB, 824 - 896 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO3E825BMPL	BASE / WHIP ENCLOSED, 3 dB, 824 - 896 MHz, .073 DIA WHIP, 17' UD, MPL CRIMP	60%	US
Hutton	132-8	Larsen	NMO3E825BTNC	BASE / WHIP ENCLOSED, 3 dB, 824 - 896 MHz, .073 DIA WHIP, 17' UD, TNC CRIMP	60%	US
Hutton	132-8	Larsen	NMO3E900B	BASE / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO3HD800B	BASE / WHIP, 3 dB, 806 - 866 MHz, .100 DIA. WHIP	60%	US
Hutton	132-8	Larsen	NMO3HD825B	BASE / WHIP, 3 dB, 824 - 896 MHz, .100 DIA	60%	US
Hutton	132-8	Larsen	NMO3HD900B	BASE / WHIP, 3 dB, 890 - 960 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMO4063CS	BASE / WHIP, 3 dBd / 5.2 dBi, 406 - 430 MHz, .100 NON-TAPERED CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO406B	BASE / WHIP, 3 dB, 406 - 420 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO406C	BASE / WHIP, 3.4 dB, 406 - 420 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO406CHW	HW COIL / WHIP, 5.5 dB, 406 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO406HWBCO	HW NMO COIL, 5.5 dB, 406 - 440 MHz	60%	US
Hutton	132-8	Larsen	NMO40B	COIL / WHIP, UNITY, 40 - 50 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO40B	COIL / WHIP, UNITY, 40 - 50 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO40BCO	NMO COIL, UNITY, 40 - 50 MHz	60%	US
Hutton	132-8	Larsen	NMO40BCO	NMO COIL, UNITY, 40 - 50 MHz	60%	US
Hutton	132-8	Larsen	NMO40BK	COIL / WHIP, UNITY, 40 - 50 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO40BK	COIL / WHIP, UNITY, 40 - 50 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO40C	COIL / WHIP, UNITY, 40 - 50 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO40C	COIL / WHIP, UNITY, 40 - 50 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO40CK	COIL / WHIP, UNITY, 40 - 50 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO40CK	COIL / WHIP, UNITY, 40 - 50 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO40CK 10	PKG OF 10, COIL / WHIP, UNITY, 40 - 50 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMO40CK 10	PKG OF 10, COIL / WHIP, UNITY, 40 - 50 MHz, 17' CX, PL259	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMO420B	BASE / WHIP, 3 dB, 420 - 440 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO420C	BASE / WHIP, 3.4 dB, 420 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO420CHW	HW COIL / WHIP, 5.5 dB, 420 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO4303CS	BASE / WHIP, 3 dBd / 5.2 dBi, 430 - 450 MHz, .100 NON-TAPERED CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO440B	BASE / WHIP, 3 dB, 440 - 460 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO440C	BASE / WHIP, 3.4 dB, 440 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO440CHW	HW NMO BASE / WHIP, 5.5 dB, 440 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO4503CS	BASE / WHIP, 3 dBd / 5.2 dBi, 450 - 470 MHz, .100 NON-TAPERED CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO4503CSUD10	BASE / WHIP, 3 dBd / 5.2 dBi, 450 - 470 MHz, 17' UD, NF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMO4503CSUD10	BASE / WHIP, 3 dBd / 5.2 dBi, 450 - 470 MHz, 17' UD, NF MOUNT, NO CONN, 10 PACK	60%	US
Hutton	132-8	Larsen	NMO450B	BASE / WHIP, 3 dB, 450 - 470 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO450BE	BASE / WHIP ENCLOSED, 3.4 dBd / 5.6 dBi, 450 - 470 MHz, .100 DIA BALCK WHIP	60%	US
Hutton	132-8	Larsen	NMO450BE	BASE / WHIP ENCLOSED, 3.4 dBd / 5.6 dBi, 450 - 470 MHz, .100 DIA BALCK WHIP	60%	US
Hutton	132-8	Larsen	NMO450BES	BASE / WHIP ENCLOSED WITH SPRING, 3 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO450BES	BASE / WHIP ENCLOSED WITH SPRING, 3 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO450BK	BASE / WHIP, 3 dB, 450 - 470 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO450C	BASE / WHIP, 3.4 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO450CHW	HW NMO BASE / WHIP, 5.5 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO450CK	BASE / WHIP, 3.4 dB, 450 - 470 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO450CK10	PKG OF 10, COIL / WHP, 3.4 dB, 450 - 470 MHz, 17' CX, PL - 259, .100 CHR WHIP	60%	US
Hutton	132-8	Larsen	NMO450HWBCO	HW NMO COIL, 5.5 dB, 440 - 490 MHz	60%	US
Hutton	132-8	Larsen	NMO4703CS	BASE / WHIP, 3 dBd / 5.2 dBi, 470 - 490 MHz, .100 NON-TAPERED CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO470B	BASE / WHIP, 3 dB, 470 - 490 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO470C	BASE / WHIP, 3.4 dB, 470 - 490 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO470CHW	HW NMO BASE / WHIP, 5.5 dB, 470 - 490 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO4903CS	BASE / WHIP, 3 dBd / 5.2 dBi, 490 - 512 MHz, .100 NON-TAPERED CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO490B	BASE / WHIP, 3 dB, 490 - 512 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO490C	BASE / WHIP, 3.4 dB, 490 - 512 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO50B	COIL / WHIP, UNITY, 50 - 54 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO50B	COIL / WHIP, UNITY, 50 - 54 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO50BCO	NMO COIL, UNITY, 50 - 54 MHz	60%	US
Hutton	132-8	Larsen	NMO50BCO	NMO COIL, UNITY, 50 - 54 MHz	60%	US
Hutton	132-8	Larsen	NMO50BK	COIL / WHIP, UNITY, 50 - 54 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO50BK	COIL / WHIP, UNITY, 50 - 54 MHz, 17' CX, PL259, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMO50C	COIL / WHIP, UNITY, 50 - 54 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO50C	COIL / WHIP, UNITY, 50 - 54 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO50CK	COIL / WHIP, UNITY, 50 - 54 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO50CK	COIL / WHIP, UNITY, 50 - 54 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO5E2400B	BASE / WHIP ENCLOSED, 5 dB, 2400 - 2500 MHz	60%	US
Hutton	132-8	Larsen	NMO5E2400BK	BASE / WHIP ENCLOSED, 5 dB, 2400 - 2500 MHz, 17' RG-58/U, NO CONN	60%	US
Hutton	132-8	Larsen	NMO5E2400BK SMA	BASE / WHIP ENCLOSED, 5 dB, 2400 - 2500 MHz, 17' RG-58/U, SMA	60%	US
Hutton	132-8	Larsen	NMO5E2400BK TNC	BASE / WHIP ENCLOSED, 5 dB, 2400 - 2500 MHz, 17' RG-58/U, TNC	60%	US
Hutton	132-8	Larsen	NMO5E825B	BASE / WHIP, ENCLOSED, 5 dB, 824 - 896 MHz, .070 DIA TWIN COIL WHIP	60%	US
Hutton	132-8	Larsen	NMO5E900B	BASE / WHIP, ENCLOSED, 5 dB, 890 - 960 MHz, .070 DIA TWIN COIL WHIP	60%	US
Hutton	132-8	Larsen	NMO5T2400B	BASE / WHIP, TWIN OPEN COIL, 7 dBi, 2400 MHz	60%	US
Hutton	132-8	Larsen	NMO5T2400B	BASE / WHIP, TWIN OPEN COIL, 7 dBi, 2400 MHz	60%	US
Hutton	132-8	Larsen	NMO5T800B	BASE / WHIP, 5 dB, 806 - 866 MHz, .100 DIA TWIN COIL WHIP	60%	US
Hutton	132-8	Larsen	NMO5T825B	BASE / WHIP, 5 dB, 824 - 896 MHz, .100 DIA TWIN COIL WHIP	60%	US
Hutton	132-8	Larsen	NMO5T900B	BASE / WHIP, 5 dB, 890 - 960 MHz, .100 DIA TWIN COIL WHIP	60%	US
Hutton	132-8	Larsen	NMO700	CHROME SPRING BASE / WHIP, ENC., 3.4 dB, 740 - 860 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO700	CHROME SPRING BASE / WHIP, ENC., 3.4 dB, 740 - 860 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO800	CHROME SPRING BASE / WHIP, ENC, 3.4 dB, 806 - 866 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO800B	SPRING BASE / WHIP, ENCLOSED, 3.4 dB, 806 - 866 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO800KUD	CHR SPRING BASE / WHIP, ENC 4.5 dB, 806 - 866 MHz, 17' UD, NO CONN, .100 CHR WHIP	60%	US
Hutton	132-8	Larsen	NMO800KUD10	10 PK, CHR SPRING BASE / WHIP, ENC, 3.4 dB, 806 - 866 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO825	CHROME SPRING BASE / WHIP, ENC, 3.4 dB, 824 - 896 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO825B	SPRING BASE / WHIP, ENCLOSED, 3.4 dB, 824 - 896 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO900	CHROME SPRING BASE / WHIP, ENC, 3.4 dB, 890 - 960 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMO900B	SPRING BASE / WHIP, ENCLOSED, 3.4 dB, 890 - 960 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOB	NMO MOUNT HARDWARE, 3/4" HOLE	60%	US
Hutton	132-8	Larsen	NMOB38	NMO MOUNT HARDWARE, A7 ADAPTER	60%	US
Hutton	132-8	Larsen	NMOBLCP	NMO MOUNT HARDWARE (LARGE CONTACT PIN)	60%	US
Hutton	132-8	Larsen	NMOBRASSRING	BRASS RING FOR NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMOC/P3E	BASE WHIP ENCLOSED, 3 dB, 824 MHz / 1850 MHz	60%	US
Hutton	132-8	Larsen	NMOC/P3EUD	BASE WHIP ENC, 3 dB, 824 MHz / 1850 MHz, 17' UD, NO CONN, ENC NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMOC/P3EUDFME	BASE WHIP ENC, 3 dB, 824 MHz / 1850 MHz, 17' UD, FME INSTALLED, ENC NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMOC/P3EUDMPL	BASE WHIP ENC, 3 dB, 824 MHz / 1850 MHz, 17' UD, MPL, ENCLOSED NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMOC/P3EUDTNC	BASE WHIP ENCLOSED, 3 dB, 824 MHz / 1850 MHz, 17' UD, TNC, ENC NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMOCAPB	RAIN CAP FOR NMO MOUNT	60%	US
Hutton	132-8	Larsen	NMOHF	NMO HIGH FREQUENCY MOUNT ONLY	60%	US
Hutton	132-8	Larsen	NMOHFCAPCRIMP	CRIMPING TOOL FOR NMOHF CAP	60%	US
Hutton	132-8	Larsen	NMOHFCAPCRIMP	CRIMPING TOOL FOR NMOHF CAP	60%	US
Hutton	132-8	Larsen	NMOK	NMO MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOK38	NMO MOUNT HARDWARE ONLY, 3/8" SNAP-IN 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOKBNC	NMO MOUNT, 17' CX, BNC	60%	US
Hutton	132-8	Larsen	NMOKDS	NMO MOUNT, 17' DS, NO CONN	60%	US
Hutton	132-8	Larsen	NMOKDSFME	NMO MOUNT, 17' DS, FME	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMOKDSMPL	NMO MOUNT, 17' DS, MPL	60%	US
Hutton	132-8	Larsen	NMOKDSN	NMO MOUNT, 17' DS, N	60%	US
Hutton	132-8	Larsen	NMOKDSPL	NMO MOUNT, 17' DS, PL259T	60%	US
Hutton	132-8	Larsen	NMOKDSTNC	NMO MOUNT, 17' DS, TNC	60%	US
Hutton	132-8	Larsen	NMOKFME	NMO MOUNT, 17' CX, FME	60%	US
Hutton	132-8	Larsen	NMOKHFCX	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, NO CONNECTOR	60%	US
Hutton	132-8	Larsen	NMOKHFCX	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, NO CONNECTOR	60%	US
Hutton	132-8	Larsen	NMOKHFCXFME	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, FME CRIMP	60%	US
Hutton	132-8	Larsen	NMOKHFCXFME	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, FME CRIMP	60%	US
Hutton	132-8	Larsen	NMOKHFCXMPL	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, MINI UHF CONNECTOR	60%	US
Hutton	132-8	Larsen	NMOKHFCXMPL	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, MINI UHF CONNECTOR	60%	US
Hutton	132-8	Larsen	NMOKHFCXPL	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, PL259 CONNECTOR	60%	US
Hutton	132-8	Larsen	NMOKHFCXPL	NMO HIGH FREQUENCY MOUNT, 17' RB58A/U, PL259 CONNECTOR	60%	US
Hutton	132-8	Larsen	NMOKHFDS	NMO MOUNT, 17' RG-58/U DUAL SHIELD, NO CONN	60%	US
Hutton	132-8	Larsen	NMOKHFUD	NMO MOUNT, 17' RG-58/U DUAL SHIELD, NO CONN	60%	US
Hutton	132-8	Larsen	NMOKHFUDFME	NMO MOUNT, 17' RG-58/U DUAL SHIELD, FME	60%	US
Hutton	132-8	Larsen	NMOKHFUDMPL	NMO MOUNT, 17' RG-58/U DUAL SHIELD, MPL	60%	US
Hutton	132-8	Larsen	NMOKHFUDTNC	NMO MOUNT, 17' RG-58/U DUAL SHIELD, TNC	60%	US
Hutton	132-8	Larsen	NMOKLCP	NMO MOUNT (LARGE CONTACT PIN), 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOKMB	NMO THK MIRROR MOUNT, 17' CX, NO CONN	60%	US
Hutton	132-8	Larsen	NMOKMPL	NMO MOUNT, 17' CX, MPL	60%	US
Hutton	132-8	Larsen	NMOKN	NMO MOUNT, 17' CX, N CRIMP	60%	US
Hutton	132-8	Larsen	NMOKNOCONN	NMO MOUNT, 17' CX, NO CONN	60%	US
Hutton	132-8	Larsen	NMOKTNC	NMO MOUNT, 17' CX, TNC	60%	US
Hutton	132-8	Larsen	NMOKUD	NMO MOUNT, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	NMOKUDFME	NMO MOUNT, 17' UD, FME	60%	US
Hutton	132-8	Larsen	NMOKUDMPL	NMO MOUNT, 17' UD, MPL	60%	US
Hutton	132-8	Larsen	NMOKUDN	NMO MOUNT, 17' UD, N	60%	US
Hutton	132-8	Larsen	NMOKUDPL	NMO MOUNT, 17' UD, PL259T	60%	US
Hutton	132-8	Larsen	NMOKUDSMA	NMO MOUNT, 17' UD, SMA MALE	60%	US
Hutton	132-8	Larsen	NMOKUDTNC	NMO MOUNT, 17' UD, TNC	60%	US
Hutton	132-8	Larsen	NMOMBNC	NMO MIRROR MOUNT, 17' UD, NO CONN	60%	US
Hutton	132-8	Larsen	NMOMM	NMO MAG MOUNT, 12' CX, UHF TYPE CONN	60%	US
Hutton	132-8	Larsen	NMOMMBNC	NMO MAG MOUNT, 12' CX, BNC	60%	US
Hutton	132-8	Larsen	NMOMMDS	NMO MAG MOUNT, 12' CX, NO CONN	60%	US
Hutton	132-8	Larsen	NMOMMDSFME	NMO MAG MOUNT, 12' CX, FME	60%	US
Hutton	132-8	Larsen	NMOMMDSMPL	NMO MAG MOUNT, 12' CX, MPL	60%	US
Hutton	132-8	Larsen	NMOMMDSN	NMO MAG MOUNT, 12' CX, N	60%	US
Hutton	132-8	Larsen	NMOMMDSTNC	NMO MAG MOUNT, 12' CX, TNC	60%	US
Hutton	132-8	Larsen	NMOMMFME	NMO MAG MOUNT, 12' CX, FME	60%	US
Hutton	132-8	Larsen	NMOMMMPL	NMO MAG MOUNT, 12' CX, MPL	60%	US
Hutton	132-8	Larsen	NMOMMNOCONN	NMO MAG MOUNT, 12' CX, NO CONN	60%	US
Hutton	132-8	Larsen	NMOMMPL	NMO MAG MOUNT, 12' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOMMR	NMO 3.5" RND MAG MOUNT, 12' CX, UHF TYPE CONN	60%	US
Hutton	132-8	Larsen	NMOMMRBNC	NMO 3.5" RND MAG MOUNT, 12' CX, BNC	60%	US
Hutton	132-8	Larsen	NMOMMRDS	NMO 3.5" RND MAG MOUNT, 12' DS, NO CONN	60%	US
Hutton	132-8	Larsen	NMOMMRDSFME	NMO 3.5" RND MAG MOUNT, 12' DS, FME	60%	US
Hutton	132-8	Larsen	NMOMMRDSMPL	NMO 3.5" RND MAG MOUNT, 12' DS, MPL	60%	US
Hutton	132-8	Larsen	NMOMMRDSN	NMO 3.5" RND MAG MOUNT, 12' DS, N	60%	US
Hutton	132-8	Larsen	NMOMMRDSPL	NMO 3.5" RND MAG MOUNT, 12' DS, PL259T	60%	US
Hutton	132-8	Larsen	NMOMMRDSTNC	NMO 3.5" RND MAG MOUNT, 12' DS, TNC	60%	US
Hutton	132-8	Larsen	NMOMMRFME	NMO 3.5" RND MAG MOUNT, 12' CX, FME	60%	US
Hutton	132-8	Larsen	NMOMMRMPL	NMO 3.5" RND MAG MOUNT, 12' CX, MPL	60%	US
Hutton	132-8	Larsen	NMOMMRN	NMO 3.5" RND MAG MOUNT, 12' CX, N	60%	US
Hutton	132-8	Larsen	NMOMMRNOCONN	NMO 3.5" RND MAG MOUNT, 12' CX, NO CONN	60%	US
Hutton	132-8	Larsen	NMOMMRPL	NMO 3.5" RND MAG MOUNT, 12' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOMMRTNC	NMO 3.5" RND MAG MOUNT, 12' CX, TNC	60%	US
Hutton	132-8	Larsen	NMOQ52C	BASE / WHIP, UNITY, 52 - 88 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOQ800B	BASE / WHIP, UNITY, 806 - 896 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOQ88C	BASE / WHIP, UNITY, 88 - 136 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOQ900B	BASE / WHIP, UNITY, 890 - 960 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOQB	BASE / WHIP, UNITY, 136 - 512 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOQBASE1B	NMOQB BASE FOR .070 DIA WHIPS	60%	US
Hutton	132-8	Larsen	NMOQBASE2B	NMOQB BASE FOR .100 DIA WHIPS	60%	US
Hutton	132-8	Larsen	NMOQBASE3B	NMOQB BASE FOR .125 DIA WHIPS	60%	US
Hutton	132-8	Larsen	NMOQQC	BASE / WHIP, UNITY, 136 - 512 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOQCK	BASE / WHIP, UNITY, 136 - 512 MHz, 17' CX, PL259, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOQSPEC	CHROME, SPEC BASE / WHIP, UNITY, 136 - 512 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOQSPEC800B	SPEC BASE / WHIP, UNITY, 806 - 896 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOQSPEC900B	SPEC BASE / WHIP, UNITY, 890 - 960 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOQSPECB	SPEC BASE / WHIP, UNITY, 136 - 512 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOQSPECCK	CHROME SPEC BASE / WHIP, UNITY, 136 - 512 MHz, 17' CX, PL259, .070 CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOQSPECCK10	CHR SPEC BASE / WHIP, UNITY, 136 - 512 MHz, 17' CX, PL259, .070 CHR WHIP, 10 PACK	60%	US
Hutton	132-8	Larsen	NMOQWFT	CHROME BASE / WHIP, UNITY, 136 - 960 MHz, ECONOMY FIELD TUNABLE ANTENNA	60%	US
Hutton	132-8	Larsen	NMOSPEC800	CHROME SPEC BASE / WHIP, 3 dB, 806 - 866 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOSPEC800B	SPEC BASE / WHIP, 3 dB, 806 - 866 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOSPEC825	CHROME SPEC BASE / WHIP, 3 dB, 824 - 896 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOSPEC825B	SPEC BASE / WHIP, 3 dB, 824 - 896 MHz, .070 DIA WHIP	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMOSPEC900	CHROME SPEC BASE / WHIP, 3 dB, 890 - 960 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOSPEC900B	SPEC BASE / WHIP, 3 dB, 890 - 960 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOTEST1	NMO MOUNT TEST ADAPTER	60%	US
Hutton	132-8	Larsen	NMOTLM	NMO CHROME TLM MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOTLMB	NMO TLM MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOTLMBNOCONN	NMO TLM MOUNT, 17' CX, NO CONN	60%	US
Hutton	132-8	Larsen	NMOTLP	NMO TLP MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOTLPDS	NMO TLP MOUNT, 17' DS, NO CONN	60%	US
Hutton	132-8	Larsen	NMOTLPFME	NMO TLP MOUNT, 17' CX, FME	60%	US
Hutton	132-8	Larsen	NMOTLPMPL	NMO TLP MOUNT, 17' CX, MPL	60%	US
Hutton	132-8	Larsen	NMOTMB	NMO CHROME TMB MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOTMBB	NMO TMB MOUNT, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	NMOTMBDS	NMO CHROME TMB MOUNT, 17' DS, NO CONN	60%	US
Hutton	132-8	Larsen	NMOU150D	NMO MOUNTED CELLULAR LOOK ALIKE VHF DISGUISE ANTENNA, 150 - 165 MHz	60%	US
Hutton	132-8	Larsen	NMOU155D	NMO MOUNTED CELLULAR LOOK ALIKE VHF DISGUISE ANTENNA, 155 - 170 MHz	60%	US
Hutton	132-8	Larsen	NMOUHFBASEB	NMO BASE, 406 - 512 MHz	60%	US
Hutton	132-8	Larsen	NMOWB150B	BASE / WHIP, 3 dB, 135 - 174 MHz, WIDE BAND, .125 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMOWB150BCO	WIDEBAND NMO COIL, 2.5 dB, 135 - 174 MHz	60%	US
Hutton	132-8	Larsen	NMOWB150BK	BASE / WHIP, 3 dB, 135 - 174 MHz, WIDE BAND, 17' CX, PL259, .125 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	NMOWB150C	BASE / WHIP, 3 dB, 135 - 174 MHz, WIDE BAND, .125 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOWB150CK	BASE / WHIP, 3 dB, 135 - 174 MHz, WIDE BAND, 17' CX, PL259, .125 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOWB150U	COIL / CHROME WHIP, 3 dB, 135 - 174 MHz, WIDE BAND	60%	US
Hutton	132-8	Larsen	NMOWB150UK	COIL / CHROME WHIP, 3 dB, 135 - 174 MHz, WIDE BAND, 17' CX, PL259, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOWB406BCO	WIDEBAND NMO COIL, 3.5 dB, 406 - 512 MHz	60%	US
Hutton	132-8	Larsen	NMOWB406C	COIL / CHROME WHIP, 3.5 dB, 406 - 430 MHz, WIDE BAND	60%	US
Hutton	132-8	Larsen	NMOWB406CK	COIL / CHR WHIP, 3.5 dB, 406 - 430 MHz, WIDE BAND, 17' CX, PL259, .100 DIA CHR WHIP	60%	US
Hutton	132-8	Larsen	NMOWB40C	WIDE BAND LOW BAND, UNITY, 5 MHz, TUNABLE BANDWIDTH, 40 - 50 MHz	60%	US
Hutton	132-8	Larsen	NMOWB430C	COIL / CHROME WHIP, 3.5 dB, 430 - 455 MHz, WIDE BAND	60%	US
Hutton	132-8	Larsen	NMOWB430CK	COIL / CHR WHIP, 3.5 dB, 430 - 455 MHz, WIDE BAND, 17' CX, PL259, .100 DIA CHR WHIP	60%	US
Hutton	132-8	Larsen	NMOWB450C	COIL / CHROME WHIP, 3.5 dB, 450 - 475 MHz, WIDE BAND	60%	US
Hutton	132-8	Larsen	NMOWB450CK	COIL / CHR WHIP, 3.5 dB, 450 - 475 MHz, WIDE BAND, 17' CX, PL259, .100 DIA CHR WHIP	60%	US
Hutton	132-8	Larsen	NMOWB470C	COIL / CHROME WHIP, 3.5 dB, 470 - 495 MHz, WIDE BAND	60%	US
Hutton	132-8	Larsen	NMOWB470CK	COIL / CHR WHIP, 3.5 dB, 470 - 495 MHz, WIDE BAND, 17' CX, PL259, .100 DIA CHR WHIP	60%	US
Hutton	132-8	Larsen	NMOWB490C	COIL / CHROME WHIP, 3.5 dB, 490 - 515 MHz, WIDE BAND	60%	US
Hutton	132-8	Larsen	NMOWB490CK	COIL / CHR WHIP, 3.5 dB, 490 - 515 MHz, WIDE BAND, 17' CX, PL259, .100 DIA CHR WHIP	60%	US
Hutton	132-8	Larsen	NMOWBQ450C	BASE / WHIP, UNITY, 450 - 470 MHz, .125 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOWBQB	SPRING BASE / WHIP, UNITY, 150 - 170 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	NMOWBQC	CHROME SPRING BASE / WHIP, UNITY, 150 - 170 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NMOWBQCK	BASE / WHIP, UNITY, 150 - 170 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	NTERM	CONNECTOR N TERMINATOR PLUG, 50 OHM	60%	US
Hutton	132-8	Larsen	OLMMNT	O RING / LM MOUNTS, 3/PKG	60%	US
Hutton	132-8	Larsen	OM150BCO	OM COIL, 144 - 174 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	OM150CK	COIL / WHIP, 2.5 dB, 144 - 174 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	OM406BCO	OM COIL, 406 - 440 MHz, 17' CX, PL259 CONN	60%	US
Hutton	132-8	Larsen	OM406CK	COIL / WHIP, 5.5 dB, 406 - 420 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	OM420CK	COIL / WHIP, 5.5 dB, 420 - 440 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	OM450BCO	OM COIL, 440 - 490 MHz, 17' CX, PL259	60%	US
Hutton	132-8	Larsen	OM450CK	COIL / WHIP, 5.5 dB, 450 - 470 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	OM470CK	COIL / WHIP, 5.5 dB, 470 - 490 MHz, 17' CX, PL259, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	OM800UD	BASE / WHIP, 3 dB, 806 - 866 MHz, 14' UD, NO CONN, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM800UDMPL	COIL / WHIP, 3 dB, 806 - 866 MHz, 14' UD, MPL, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM800UDTNC	COIL / WHIP, 3 dB, 806 - 866 MHz, 14' UD, MPL, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM825UD	BASE / WHIP, 3 dB, 825 - 896 MHz, 14' UD, NO CONN	60%	US
Hutton	132-8	Larsen	OM825UDMPL	COIL / WHIP, 3 dB, 824 - 896 MHz, 14' UD, MPL, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM825UDTNC	COIL / WHIP, 3 dB, 824 - 896 MHz, 14' UD, MPL, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM900UD	BASE / WHIP, 3 dB, 890 - 960 MHz, 14' UD, NO CONN, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM900UDMPL	COIL / WHIP, 3 dB, 890 - 960 MHz, 14' UD, MPL, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	OM900UDTNC	COIL / WHIP, 3 dB, 890 - 960 MHz, 14' UD, TNC, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	ONMOANT	O RING / NMO COILS & BASES, 3/PKG	60%	US
Hutton	132-8	Larsen	ONMOMNT	O RING / NMO MOUNT HARDWARE, 3/PKG	60%	US
Hutton	132-8	Larsen	OPOMNT	O RING / NMO PO MOUNT, 3/PKG	60%	US
Hutton	132-8	Larsen	PA18900N	PANEL, 8 dBi, 890 - 960 MHz, N CONN, SINGLE ELEMENT	60%	US
Hutton	132-8	Larsen	PAMOUNT	PANEL MOUNT BRACKET	60%	US
Hutton	132-8	Larsen	PL258	CONNECTOR, DOUBLE FEMALE BARREL	60%	US
Hutton	132-8	Larsen	PL259	CONNECTOR, SOLDER PHENOLIC DIELEC, RG-58	60%	US
Hutton	132-8	Larsen	PL25925	PKG OF 25 PL259 CONNECTORS	60%	US
Hutton	132-8	Larsen	PL25925	PKG OF 25 PL259 CONNECTORS	60%	US
Hutton	132-8	Larsen	PL2598	CONNECTOR, SOLDER TEFLON DIELEC, RG-58 AND RG-213	60%	US
Hutton	132-8	Larsen	PL2598PHN	CONNECTOR, SOLDER PHENOLIC DIELEC, RG-58 AND RG-213	60%	US
Hutton	132-8	Larsen	PL259T	CONNECTOR, SOLDER TEFLON DIELEC, RG-58	60%	US
Hutton	132-8	Larsen	PL259T25	PKG OF 25 PL259T CONNECTORS	60%	US
Hutton	132-8	Larsen	PL259T25	PKG OF 25 PL259T CONNECTORS	60%	US
Hutton	132-8	Larsen	PLCP	CONNECTOR, UHF CRIMP PLUG, 58/U	60%	US
Hutton	132-8	Larsen	PO150B	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA BLACK WHIP	60%	US
Hutton	132-8	Larsen	PO150BCO	PO COIL, 144 - 174 MHz	60%	US
Hutton	132-8	Larsen	PO150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	PO150C	COIL / WHIP, 3 dB, 144 - 174 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	PO406C	BASE / WHIP, 3.4 dB, 406 - 420 MHz, .100 DIA CHROME WHIP	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	PO420C	BASE / WHIP, 3.4 dB, 420 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	PO440C	BASE / WHIP, 3.4 dB, 440 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	PO450C	BASE / WHIP, 3.4 dB, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	PO470C	BASE / WHIP, 3.4 dB, 470 - 490 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	POB	PO MOUNT HARDWARE ONLY	60%	US
Hutton	132-8	Larsen	POMM	PO MAG MOUNT, 12' CX, UHF TYPE CONN	60%	US
Hutton	132-8	Larsen	POMMR	PO RND MAG MOUNT, 12' CX, UHF TYPE CONN	60%	US
Hutton	132-8	Larsen	POUHFBASEB	PO BASE, 406 - 512 MHz	60%	US
Hutton	132-8	Larsen	PQ	PL259 BASE / WHIP, UNITY, 144 - 512 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	Q	CHROME CONE / WHIP, UNITY, 136 - 512 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	Q52	CHROME Q BASE / WHIP, UNITY, 52 - 88 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	Q800	Q CONE .100 & W030, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	Q88	CHROME Q BASE / WHIP, UNITY, 88 - 136 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	Q900	Q CONE .100 & W035, 890 - 960 MHz	60%	US
Hutton	132-8	Larsen	QB	CONE / WHIP, UNITY, 136 - 512 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	QCONE.073	CHROME Q BASE, .073 DIA	60%	US
Hutton	132-8	Larsen	QCONE.073B	Q BASE, .073 DIA	60%	US
Hutton	132-8	Larsen	QCONE.100	CHROME Q BASE, .100 DIA	60%	US
Hutton	132-8	Larsen	QCONE.100B	Q BASE, .100 DIA	60%	US
Hutton	132-8	Larsen	QCONE.125	CHROME Q BASE, .125 DIA	60%	US
Hutton	132-8	Larsen	QCONE.125B	Q BASE, .125 DIA	60%	US
Hutton	132-8	Larsen	R380.500.100	DIPOLE, 2400 - 2500 MHz, 2 dBi, 3.94" COAX, RIGHT ANGLE MMS	60%	US
Hutton	132-8	Larsen	R380.500.102	DIPOLE, 2400 - 2500 MHz, 2 dBi, DIRECT MCX PLUG (MALE)	60%	US
Hutton	132-8	Larsen	R380.500.104	TABLE TOP DIPOLE, 2400 - 2500 MHz, 2 dBi, SHF 2.6 COAX, SMB	60%	US
Hutton	132-8	Larsen	R380.500.109	DIPOLE, 2400 - 2500 MHz, 2 dBi, DIRECT SMA PLUG (MALE)	60%	US
Hutton	132-8	Larsen	R380.500.125	MOLDED DIPOLE, 2 dBi, 2400 - 2500 MHz, SMA FEMALE, 2.4" HEIGHT	60%	US
Hutton	132-8	Larsen	R380.500.217	PLANAR ARRAY, VERT POLARIZATION, 2400 - 2500 MHz, 15 / 14 dBi, 6.5' SHF142, N	60%	US
Hutton	132-8	Larsen	R380.500.218	PLANAR ARRAY, HOR POLARIZATION, 2400 - 2500 MHz, 15 / 14 dBi, 6.5' SHF142, N	60%	US
Hutton	132-8	Larsen	R380.500.219	RADOME OMNI, 6 dBi, 2400 - 2500 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.500.219	RADOME OMNI, 6 dBi, 2400 - 2500 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.500.219	RADOME OMNI, 6 dBi, 2400 - 2500 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.500.220	RADOME OMNI, 8 dBi, 2400 - 2500 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.500.220	RADOME OMNI, 8 dBi, 2400 - 2500 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.500.312	MAST / WALL MOUNT DIRECTIONAL PATCH, 7.5 dBi, 2400 - 2500 MHz, SMA JACK (FEMALE)	60%	US
Hutton	132-8	Larsen	R380.500.312	MAST / WALL MOUNT DIRECTIONAL PATCH, 7.5 dBi, 2400 - 2500 MHz, SMA JACK (FEMALE)	60%	US
Hutton	132-8	Larsen	R380.500.501	OMNI CEILING, 2 dBi, 2400 - 2500 MHz, 12" PLENUM RATED CABLE	60%	US
Hutton	132-8	Larsen	R380.600.101	BULKHEAD FEED STRAIGHT DIPOLE, 5150 - 5350 MHz, 1 dBi, 4" RG-178, UMP	60%	US
Hutton	132-8	Larsen	R380.600.101	BULKHEAD FEED STRAIGHT DIPOLE, 5150 - 5350 MHz, 1 dBi, 4" RG-178, UMP	60%	US
Hutton	132-8	Larsen	R380.600.200	RADOME OMNI, 10 dBi, 5200 - 5350 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.600.200	RADOME OMNI, 10 dBi, 5200 - 5350 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.600.200	RADOME OMNI, 10 dBi, 5200 - 5350 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.600.201	RADOME OMNI, 6 dBi, 5200 - 5350 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.600.201	RADOME OMNI, 6 dBi, 5200 - 5350 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.600.201	RADOME OMNI, 6 dBi, 5200 - 5350 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.700.203	PLANAR ARRAY, VERT POLARIZATION, 5725 - 5825 MHz, 20 / 19 dBi, 6.5' SHF142, N	60%	US
Hutton	132-8	Larsen	R380.700.204	PLANAR ARRAY, HOR POLARIZATION, 5725 - 5825 MHz, 20 / 19 dBi, 6.5' SHF142, N	60%	US
Hutton	132-8	Larsen	R380.700.205	RADOME OMNI, 10 dBi, 5725 - 5875 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.700.205	RADOME OMNI, 10 dBi, 5725 - 5875 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.700.205	RADOME OMNI, 10 dBi, 5725 - 5875 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.700.206	RADOME OMNI, 6 dBi, 5725 - 5825 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.700.206	RADOME OMNI, 6 dBi, 5725 - 5825 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.700.206	RADOME OMNI, 6 dBi, 5725 - 5825 MHz, N FEMALE	60%	US
Hutton	132-8	Larsen	R380.900.323	TRI BAND SMR/CELLULAR/PCS STEALTH BLADE, 806 - 890 / 1850 - 1990 MHz, 10' RG-174, FME	60%	US
Hutton	132-8	Larsen	R380.900.323	TRI BAND SMR/CELLULAR/PCS STEALTH BLADE, 806 - 890 / 1850 - 1990 MHz, 10' RG-174, FME	60%	US
Hutton	132-8	Larsen	R380.900.323	TRI BAND SMR/CELLULAR/PCS STEALTH BLADE, 806 - 890 / 1850 - 1990 MHz, 10' RG-174, FME	60%	US
Hutton	132-8	Larsen	R380.900.903	OMNI CEILING, 2 dBi, 5200 - 5800 MHz, 12" PLENUM RATED CABLE	60%	US
Hutton	132-8	Larsen	R445.999.001	N GROUNDING RING	60%	US
Hutton	132-8	Larsen	R445.999.001	N GROUNDING RING	60%	US
Hutton	132-8	Larsen	R445.999.100	REPLACABLE GAS CAPSULE FOR R445.G00.000, DC SPARKOVER VOLTAGE 230 +/- 20%	60%	US
Hutton	132-8	Larsen	R445.999.101	REPLACABLE GAS CAPSULE FOR R445.G00.000, DC SPARKOVER VOLTAGE 350 +/- 20%	60%	US
Hutton	132-8	Larsen	R445.999.102	REPLACABLE GAS CAPSULE FOR R445.G00.000, DC SPARKOVER VOLTAGE 90 +/- 20%	60%	US
Hutton	132-8	Larsen	R445.999.103	REPLACABLE GAS CAPSULE FOR R445.G00.000, DC SPARKOVER VOLTAGE 350 +/- 20%	60%	US
Hutton	132-8	Larsen	R445.999.105	REPLACABLE GAS CAPSULE FOR R445.G00.000, DC SPARKOVER VOLTAGE 230 +/- 20%	60%	US
Hutton	132-8	Larsen	R445.G00.000	GAS DISCHARGE LIGHTNING PROTECTOR, DC-2.5 GHz, GPS, NF BULK / NF	60%	US
Hutton	132-8	Larsen	R445.G00.002	R445.G00.000 GDT LIGHTNING PROTECTOR WITH R445.999.100 GAS CAPSULE	60%	US
Hutton	132-8	Larsen	R445.G00.003	R445.G00.000 GDT LIGHTNING PROTECTOR WITH R445.999.101 GAS CAPSULE	60%	US
Hutton	132-8	Larsen	R445.G00.004	R445.G00.000 GDT LIGHTNING PROTECTOR WITH R445.999.102 GAS CAPSULE	60%	US
Hutton	132-8	Larsen	R445.G00.005	R445.G00.000 GDT LIGHTNING PROTECTOR WITH R445.999.103 GAS CAPSULE	60%	US
Hutton	132-8	Larsen	R445.G00.006	R445.G00.000 GDT LIGHTNING PROTECTOR WITH R445.999.105 GAS CAPSULE	60%	US
Hutton	132-8	Larsen	R445.Q00.000	QWS LIGHTNING PROTECTOR, 1710 - 1990 MHz, PCS AND DCS, NF BULK / NF	60%	US
Hutton	132-8	Larsen	R445.Q00.001	QWS LIGHTNING PROTECTOR, 824 - 960 MHz, AMPS, GSM, NF BULK / NF	60%	US
Hutton	132-8	Larsen	R445.Q00.004	QWS LIGHTNING PROTECTOR, 2400 - 2500 MHz, ISM / 802.11b, NF / NF	60%	US
Hutton	132-8	Larsen	R445.Q00.004	QWS LIGHTNING PROTECTOR, 2400 - 2500 MHz, ISM / 802.11b, NF / NF	60%	US
Hutton	132-8	Larsen	R445.Q00.101	QWS LIGHTNING PROTECTOR, 824 - 960 MHz, AMPS, GSM, NF BULK/NM	60%	US
Hutton	132-8	Larsen	RG174	CABLE, RG-174, 26 SOLID FOIL / BRAID-POLY MINI CABLE	60%	US
Hutton	132-8	Larsen	RG213	CABLE, RG-213, RG-8 STRANDED, CTR POLYETHYLENE DIELECTRIC	60%	US
Hutton	132-8	Larsen	RGFB1ANT	GASKETS FOR FB1, 3/PKG	60%	US
Hutton	132-8	Larsen	RGNMOANT	GASKETS FOR NMO COIL, 3/PKG	60%	US

Hutton Communications, Inc.  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	RGOMANT	GASKETS FOR OM, 3/PKG	60%	US
Hutton	132-8	Larsen	RGPOMNT	GASKETS FOR PO MOUNT, 3/PKG	60%	US
Hutton	132-8	Larsen	RGSBKmnt	GASKETS FOR SBK, 3/PKG	60%	US
Hutton	132-8	Larsen	RGSS	SUPERSEAL GASKETS FOR COILS, 3/PKG	60%	US
Hutton	132-8	Larsen	RGLMmnt	GASKET FOR TLM MOUNT, 1/PKG	60%	US
Hutton	132-8	Larsen	SB2400MMCX3	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 3' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	SB2400MMCX6	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 6' RG-174, MMCX	60%	US
Hutton	132-8	Larsen	SB2400SMA3	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 3' RG-174, SMA	60%	US
Hutton	132-8	Larsen	SB2400SMA6	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 6' RG-174, SMA	60%	US
Hutton	132-8	Larsen	SB2400SMB3	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 3' RG-174, SMB	60%	US
Hutton	132-8	Larsen	SB2400SMB6	STEALTH BLADE, UNITY / 2.14 dBi, 2400 - 2500 MHz, 6' RG-174, SMB	60%	US
Hutton	132-8	Larsen	SB450FME12	STEALTH BLADE, 450 - 470 MHz, 12' RG-316, FME CRIMP	60%	US
Hutton	132-8	Larsen	SB450FME3	STEALTH BLADE, 450 - 470 MHz, 3' RG-316, FME CRIMP	60%	US
Hutton	132-8	Larsen	SB800FME12	STEALTH BLADE, 806 - 896 MHz, 12' RG-174, FME	60%	US
Hutton	132-8	Larsen	SB800FME3	STEALTH BLADE, 806 - 896 MHz, 3' RG-174, FME CRIMP	60%	US
Hutton	132-8	Larsen	SB800MPL12	STEALTH BLADE, 806 - 896 MHz, 12' RG-174, MPL CRIMP	60%	US
Hutton	132-8	Larsen	SB800MPL3	STEALTH BLADE, 806 - 896 MHz, 3' RG-174, MPL CRIMP	60%	US
Hutton	132-8	Larsen	SB800TNC12	STEALTH BLADE, 806 - 896 MHz, 12' RG-174, TNC CRIMP	60%	US
Hutton	132-8	Larsen	SB800TNC3	STEALTH BLADE, 806 - 896 MHz, 3' RG-174, TNC CRIMP	60%	US
Hutton	132-8	Larsen	SB90012	STEALTH BLADE, 890 - 960 MHz, 12' RG-174, NO CONN	60%	US
Hutton	132-8	Larsen	SB9003	STEALTH BLADE, 890 - 960 MHz, 3' RG-174, NO CONN	60%	US
Hutton	132-8	Larsen	SB900FME12	STEALTH BLADE, 890 - 960 MHz, 12' RG-174, FME CRIMP	60%	US
Hutton	132-8	Larsen	SB900FME3	STEALTH BLADE, 890 - 960 MHz, 3' RG-174, FME CRIMP	60%	US
Hutton	132-8	Larsen	SB900MPL12	STEALTH BLADE, 890 - 960 MHz, 12' RG-174, MPL	60%	US
Hutton	132-8	Larsen	SB900MPL3	STEALTH BLADE, 890 - 960 MHz, 3' RG-174, MPL CRIMP	60%	US
Hutton	132-8	Larsen	SB900SMA12	STEALTH BLADE, 890 - 960 MHz, 12' RG-174, SMA MALE	60%	US
Hutton	132-8	Larsen	SB900SMA3	STEALTH BLADE, 890 - 960 MHz, 3' RG-174, SMA MALE	60%	US
Hutton	132-8	Larsen	SBA	SPEED BOAT MOUNT / WHIP, UNITY (SPECIFY FREQUENCY)	60%	US
Hutton	132-8	Larsen	SBK	SAIL BOAT MOUNTING KIT	60%	US
Hutton	132-8	Larsen	SMAAP174	CONNECTOR, SMA ANGLE PLUG, 174/U	60%	US
Hutton	132-8	Larsen	SMACJ	CONNECTOR, SMA CRIMP JACK, 58/U	60%	US
Hutton	132-8	Larsen	SMACP174	CONNECTOR, SMA CRIMP PLUG, 174/U	60%	US
Hutton	132-8	Larsen	SMACP58	CONNECTOR, SMA CRIMP PLUG, 58/U	60%	US
Hutton	132-8	Larsen	SPANNER	SPANNER WRENCH FOR PO OR NMO MOUNTS	60%	US
Hutton	132-8	Larsen	SPDA15832	DIPOLE - CENTER FED, 824 - 894 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPDA171800	DIPOLE - CENTER FED, 1710 - 1850 MHz, TNC, 6 1/2"	60%	US
Hutton	132-8	Larsen	SPDA171900	DIPOLE - CENTER FED, 1850 - 1990 MHz, TNC, 6 1/2"	60%	US
Hutton	132-8	Larsen	SPDA172400	DIPOLE - CENTER FED, 2400 - 2500 MHz, TNC, 4"	60%	US
Hutton	132-8	Larsen	SPDA17832	DIPOLE - CENTER FED, 824 - 894 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPDA17918	DIPOLE - CENTER FED, 872 - 964 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPDA17RP2400	DIPOLE - CENTER FED, 2400 - 2500 MHz, TNC RP, 4"	60%	US
Hutton	132-8	Larsen	SPDA17RP918	DIPOLE - CENTER FED, 890 - 960 MHz, TNC RP, 8"	60%	US
Hutton	132-8	Larsen	SPDA241800	DIPOLE - CENTER FED, 1710 - 1850 MHz, SMA, 6 1/2"	60%	US
Hutton	132-8	Larsen	SPDA241900	DIPOLE - CENTER FED, 1850 - 1990 MHz, SMA, 6 1/2"	60%	US
Hutton	132-8	Larsen	SPDA242400	DIPOLE - CENTER FED, 2400 - 2500 MHz, SMA, 4"	60%	US
Hutton	132-8	Larsen	SPDA24832	DIPOLE - CENTER FED, 824 - 894 MHz, SMA, 9"	60%	US
Hutton	132-8	Larsen	SPDA24832	DIPOLE - CENTER FED, 824 - 894 MHz, SMA, 9"	60%	US
Hutton	132-8	Larsen	SPDA24918	DIPOLE - CENTER FED, 890 - 960 MHz, SMA, 8"	60%	US
Hutton	132-8	Larsen	SPDA24RP2400	DIPOLE - CENTER FED, 2400 - 2500 MHz, SMARP, 4"	60%	US
Hutton	132-8	Larsen	SPDA24RP918	DIPOLE - CENTER FED, 890 - 960 MHz, SMARP, 8"	60%	US
Hutton	132-8	Larsen	SPDP242400	DIPOLE - CENTER FED, FIXED RIGHT ANGLE, 2400 - 2500 MHz, N FEMALE, 3.5"	60%	US
Hutton	132-8	Larsen	SPDP24RP2400	DIPOLE - CENTER FED, FIXED RIGHT ANGLE, 2400 - 2500 MHz, N FEMALE, 3.5"	60%	US
Hutton	132-8	Larsen	SPEN14832	WHIP - END FED, 806 - 866 MHz, M7X1.0, 7"	60%	US
Hutton	132-8	Larsen	SPEN14918	WHIP - END FED, 890 - 960 MHz, M7X1.0, 6"	60%	US
Hutton	132-8	Larsen	SPHE10FREQ	HELICAL - 1/4 WAVE CUSTOM TUNED, SPECIFY FREQ., 30 - 80 MHz, 1/4-32x3/16, 11"	60%	US
Hutton	132-8	Larsen	SPHE15FREQ	HELICAL - 1/4 WAVE CUSTOM TUNED, SPECIFY FREQ., 30 - 80 MHz, BNC, 11"	60%	US
Hutton	132-8	Larsen	SPHE17FREQ	HELICAL - 1/4 WAVE CUSTOM TUNED, SPECIFY FREQ., 30 - 80 MHz, TNC, 11"	60%	US
Hutton	132-8	Larsen	SPHL10144	HELICAL - STANDARD - 1/4 WAVE, 138 - 150 MHz, 1/4-32x3/16, 8"	60%	US
Hutton	132-8	Larsen	SPHL10152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, 1/4-32x3/16, 8"	60%	US
Hutton	132-8	Larsen	SPHL10156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, 1/4-32x3/16, 8"	60%	US
Hutton	132-8	Larsen	SPHL10160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, 1/4-32x3/16, 8"	60%	US
Hutton	132-8	Larsen	SPHL10167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, 1/4-32x3/16, 8"	60%	US
Hutton	132-8	Larsen	SPHL10221	HELICAL - STANDARD - 1/4 WAVE, 212 - 230 MHz, 1/4-32X3/16, 8"	60%	US
Hutton	132-8	Larsen	SPHL10FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, 1/4-32x3/16, 7"	60%	US
Hutton	132-8	Larsen	SPHL14136	HELICAL - STANDARD - 1/4 WAVE, 130 - 142 MHz, M7X1.0, 8"	60%	US
Hutton	132-8	Larsen	SPHL14152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, M7X1.0, 8"	60%	US
Hutton	132-8	Larsen	SPHL14156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, M7X1.0, 8"	60%	US
Hutton	132-8	Larsen	SPHL14160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, M7X1.0, 8"	60%	US
Hutton	132-8	Larsen	SPHL14167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, M7X1.0, 8"	60%	US
Hutton	132-8	Larsen	SPHL14FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, M7X1.0, 8"	60%	US
Hutton	132-8	Larsen	SPHL15144	HELICAL - STANDARD - 1/4 WAVE, 138 - 150 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL15152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL15156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL15160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL15167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL15FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, BNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL16144	HELICAL - STANDARD - 1/4 WAVE, 138 - 150 MHz, BNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL16152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, BNC COVERED, 8"	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	SPHL16156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, BNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL16160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, BNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL16167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, BNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL16FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, BNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL17152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL17156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL17160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL17167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL17FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, TNC, 8"	60%	US
Hutton	132-8	Larsen	SPHL18152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, TNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL18156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, TNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL18160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, TNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL18167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, TNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL18FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, TNC COVERED, 8"	60%	US
Hutton	132-8	Larsen	SPHL20FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, SMA M T1, 8"	60%	US
Hutton	132-8	Larsen	SPHL21152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, SMA F T1, 8"	60%	US
Hutton	132-8	Larsen	SPHL21156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, SMA F T1, 7"	60%	US
Hutton	132-8	Larsen	SPHL21160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, SMA F T1, 7"	60%	US
Hutton	132-8	Larsen	SPHL21167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, SMA F T1, 7"	60%	US
Hutton	132-8	Larsen	SPHL21221	HELICAL - STANDARD - 1/4 WAVE, 214 - 228 MHz, SMA F T1, 8"	60%	US
Hutton	132-8	Larsen	SPHL21FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 138 - 221 MHz, SMA F T1, 8"	60%	US
Hutton	132-8	Larsen	SPHL22152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, SMA F T2, 8"	60%	US
Hutton	132-8	Larsen	SPHL22156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, SMA F T2, 8"	60%	US
Hutton	132-8	Larsen	SPHL22160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, SMA F T2, 8"	60%	US
Hutton	132-8	Larsen	SPHL22167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, SMA F T2, 8"	60%	US
Hutton	132-8	Larsen	SPHL22FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, SMA F T2, 7"	60%	US
Hutton	132-8	Larsen	SPHL23152	HELICAL - STANDARD - 1/4 WAVE, 146 - 158 MHz, SMA F T3, 7"	60%	US
Hutton	132-8	Larsen	SPHL23156	HELICAL - STANDARD - 1/4 WAVE, 150 - 162 MHz, SMA F T3, 7"	60%	US
Hutton	132-8	Larsen	SPHL23160	HELICAL - STANDARD - 1/4 WAVE, 154 - 166 MHz, SMA F T3, 7"	60%	US
Hutton	132-8	Larsen	SPHL23167	HELICAL - STANDARD - 1/4 WAVE, 160 - 174 MHz, SMA F T3, 7"	60%	US
Hutton	132-8	Larsen	SPHL23FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, SMA F T3, 7"	60%	US
Hutton	132-8	Larsen	SPHL24FT	HELICAL - STANDARD - 1/4 WAVE, FIELD TUNABLE, 136 - 221 MHz, SMA M T2, 7"	60%	US
Hutton	132-8	Larsen	SPHS10152	HELICAL SHORT - 1/4 WAVE, 148 - 156 MHz, 1/4-32x3/16, 4"	60%	US
Hutton	132-8	Larsen	SPHS10156	HELICAL SHORT - 1/4 WAVE, 152 - 160 MHz, 1/4-32x3/16, 4"	60%	US
Hutton	132-8	Larsen	SPHS10160	HELICAL SHORT - 1/4 WAVE, 156 - 164 MHz, 1/4-32x3/16, 4"	60%	US
Hutton	132-8	Larsen	SPHS10167	HELICAL SHORT - 1/4 WAVE, 162 - 172 MHz, 1/4-32x3/16, 4"	60%	US
Hutton	132-8	Larsen	SPHS10221	HELICAL SHORT - 1/4 WAVE, 214 - 228 MHz, 1/4-32x3/16, 4"	60%	US
Hutton	132-8	Larsen	SPHS10420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, 1/4-32x3/16, 2.75"	60%	US
Hutton	132-8	Larsen	SPHS10450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, 1/4-32x3/16, 2.75"	60%	US
Hutton	132-8	Larsen	SPHS10470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, 1/4-32x3/16, 2.75"	60%	US
Hutton	132-8	Larsen	SPHS10490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, 1/4-32x3/16, 2.75"	60%	US
Hutton	132-8	Larsen	SPHS14152	HELICAL SHORT - 1/4 WAVE, 146 - 158 MHz, M7x1.0, 4"	60%	US
Hutton	132-8	Larsen	SPHS14156	HELICAL SHORT - 1/4 WAVE, 152 - 160 MHz, M7x1.0, 3"	60%	US
Hutton	132-8	Larsen	SPHS14160	HELICAL SHORT - 1/4 WAVE, 156 - 164 MHz, M7x1.0, 4"	60%	US
Hutton	132-8	Larsen	SPHS14167	HELICAL SHORT - 1/4 WAVE, 162 - 172 MHz, M7x1.0, 4"	60%	US
Hutton	132-8	Larsen	SPHS14420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, M7x1.0, 3"	60%	US
Hutton	132-8	Larsen	SPHS14450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, M7x1.0, 3"	60%	US
Hutton	132-8	Larsen	SPHS14470	HELICAL SHORT - 1/4 WAVE, 460 - 500 MHz, M7x1.0, 3"	60%	US
Hutton	132-8	Larsen	SPHS14490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, M7x1.0, 3"	60%	US
Hutton	132-8	Larsen	SPHS14832	HELICAL SHORT - 1/4 WAVE, 800 - 865 MHz, M7x1.0, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS15152	HELICAL SHORT - 1/4 WAVE, 146 - 158 MHz, BNC, 4"	60%	US
Hutton	132-8	Larsen	SPHS15156	HELICAL SHORT - 1/4 WAVE, 152 - 160 MHz, BNC, 4"	60%	US
Hutton	132-8	Larsen	SPHS15160	HELICAL SHORT - 1/4 WAVE, 156 - 164 MHz, BNC, 4"	60%	US
Hutton	132-8	Larsen	SPHS15167	HELICAL SHORT - 1/4 WAVE, 162 - 172 MHz, BNC, 4"	60%	US
Hutton	132-8	Larsen	SPHS15420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, BNC, 3"	60%	US
Hutton	132-8	Larsen	SPHS15450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, BNC, 3"	60%	US
Hutton	132-8	Larsen	SPHS15470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, BNC, 3"	60%	US
Hutton	132-8	Larsen	SPHS15490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, BNC, 3"	60%	US
Hutton	132-8	Larsen	SPHS16152	HELICAL SHORT - 1/4 WAVE, 148 - 156 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS16156	HELICAL SHORT - 1/4 WAVE, 152 - 160 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS16160	HELICAL SHORT - 1/4 WAVE, 156 - 164 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS16167	HELICAL SHORT - 1/4 WAVE, 162 - 172 MHz, BNC COVERED, 4"	60%	US
Hutton	132-8	Larsen	SPHS16420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS16450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS16470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS16490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, BNC COVERED, 3"	60%	US
Hutton	132-8	Larsen	SPHS20832	HELICAL SHORT - 1/4 WAVE, 800 - 864 MHz, SMA M T1, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS20918	HELICAL SHORT - 1/4 WAVE, 872 - 954 MHz, SMA M T1, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS21152	HELICAL SHORT - 1/4 WAVE, 146 - 158 MHz, SMA F T1, 4"	60%	US
Hutton	132-8	Larsen	SPHS21156	HELICAL SHORT - 1/4 WAVE, 152 - 160 MHz, SMA F T1, 4"	60%	US
Hutton	132-8	Larsen	SPHS21160	HELICAL SHORT - 1/4 WAVE, 156 - 164 MHz, SMA F T1, 4"	60%	US
Hutton	132-8	Larsen	SPHS21167	HELICAL SHORT - 1/4 WAVE, 162 - 172 MHz, SMA F T1, 4"	60%	US
Hutton	132-8	Larsen	SPHS21420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, SMA F T1, 3"	60%	US
Hutton	132-8	Larsen	SPHS21450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, SMA F T1, 3"	60%	US
Hutton	132-8	Larsen	SPHS21470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, SMA F T1, 3"	60%	US
Hutton	132-8	Larsen	SPHS21490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, SMA F T1, 3"	60%	US
Hutton	132-8	Larsen	SPHS21832	HELICAL SHORT - 1/4 WAVE, 800 - 864 MHz, SMA F T1, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS21918	HELICAL SHORT - 1/4 WAVE, 872 - 954 MHz, SMA F T1, 2 3/4"	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	SPHS22152	HELICAL SHORT - 1/4 WAVE, 148 - 156 MHz, SMA F T2, 4"	60%	US
Hutton	132-8	Larsen	SPHS22156	HELICAL SHORT - 1/4 WAVE, 152 - 160 MHz, SMA F T2, 4"	60%	US
Hutton	132-8	Larsen	SPHS22160	HELICAL SHORT - 1/4 WAVE, 156 - 164 MHz, SMA F T2, 4"	60%	US
Hutton	132-8	Larsen	SPHS22167	HELICAL SHORT - 1/4 WAVE, 162 - 172 MHz, SMA F T2, 4"	60%	US
Hutton	132-8	Larsen	SPHS22420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, SMA F T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS22450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, SMA F T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS22470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, SMA F T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS22490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, SMA F T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS22832	HELICAL SHORT - 1/4 WAVE, 800 - 864 MHz, SMA F T2, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS22918	HELICAL SHORT - 1/4 WAVE, 872 - 954 MHz, SMA F T2, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS23420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, SMA F T3, 3"	60%	US
Hutton	132-8	Larsen	SPHS23450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, SMA F T3, 3"	60%	US
Hutton	132-8	Larsen	SPHS23470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, SMA F T3, 3"	60%	US
Hutton	132-8	Larsen	SPHS23490	HELICAL SHORT - 1/4 WAVE, 475 - 515 MHz, SMA F T3, 3"	60%	US
Hutton	132-8	Larsen	SPHS23832	HELICAL SHORT - 1/4 WAVE, 800 - 864 MHz, SMA F T3, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS23918	HELICAL SHORT - 1/4 WAVE, 872 - 954 MHz, SMA F T3, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS24420	HELICAL SHORT - 1/4 WAVE, 403 - 437 MHz, SMA M T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS24450	HELICAL SHORT - 1/4 WAVE, 432 - 468 MHz, SMA M T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS24470	HELICAL SHORT - 1/4 WAVE, 462 - 498 MHz, SMA M T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS24490	HELICAL SHORT - 1/4 WAVE, 470 - 512 MHz, SMA M T2, 3"	60%	US
Hutton	132-8	Larsen	SPHS24832	HELICAL SHORT - 1/4 WAVE, 800 - 864 MHz, SMA M T2, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPHS24918	HELICAL SHORT - 1/4 WAVE, 872 - 954 MHz, SMA M T2, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPKR1	WEATHERPROOF SPEAKER	60%	US
Hutton	132-8	Larsen	SPNY15450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, BNC, 6"	60%	US
Hutton	132-8	Larsen	SPNY15832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, BNC, 3"	60%	US
Hutton	132-8	Larsen	SPNY15918	WHIP - STANDARD - 1/4 WAVE, 872 - 964 MHz, BNC, 3"	60%	US
Hutton	132-8	Larsen	SPNY17450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, TNC, 6"	60%	US
Hutton	132-8	Larsen	SPNY17832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, TNC, 3"	60%	US
Hutton	132-8	Larsen	SPNY17918	WHIP - STANDARD - 1/4 WAVE, 872 - 964 MHz, TNC, 3"	60%	US
Hutton	132-8	Larsen	SPRING	CHROME SHOCK SPRING	60%	US
Hutton	132-8	Larsen	SPRINGB	SHOCK SPRING	60%	US
Hutton	132-8	Larsen	SPWH10420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, 1/4-32x3/16, 6"	60%	US
Hutton	132-8	Larsen	SPWH10450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, 1/4-32x3/16, 6"	60%	US
Hutton	132-8	Larsen	SPWH10470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, 1/4-32x3/16, 6"	60%	US
Hutton	132-8	Larsen	SPWH10490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, 1/4-32x3/16, 6"	60%	US
Hutton	132-8	Larsen	SPWH10FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, 1/4-32x3/16, 8"	60%	US
Hutton	132-8	Larsen	SPWH14420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, M7x1.0, 6"	60%	US
Hutton	132-8	Larsen	SPWH14450	WHIP - STANDARD - 1/4 WAVE, 423 - 477 MHz, M7x1.0, 6"	60%	US
Hutton	132-8	Larsen	SPWH14470	WHIP - STANDARD - 1/4 WAVE, 450 - 510 MHz, M7x1.0, 6"	60%	US
Hutton	132-8	Larsen	SPWH14490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, M7x1.0, 6"	60%	US
Hutton	132-8	Larsen	SPWH14832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, M7x1.0, 3"	60%	US
Hutton	132-8	Larsen	SPWH14FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, M7x1.0, 6"	60%	US
Hutton	132-8	Larsen	SPWH15420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, BNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH15450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, BNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH15470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, BNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH15490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, BNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH15832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, BNC, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPWH15FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, BNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH16420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, BNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH16450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, BNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH16470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, BNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH16490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, BNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH16FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, BNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH17420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, TNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH17450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, TNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH17470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, TNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH17490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, TNC, 6"	60%	US
Hutton	132-8	Larsen	SPWH17832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, TNC, 3.5"	60%	US
Hutton	132-8	Larsen	SPWH17FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, BNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH18420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, TNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH18450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, TNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH18470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, TNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH18490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, TNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH18832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, TNC COVERED, 3.5"	60%	US
Hutton	132-8	Larsen	SPWH18FT	WHIP - STANDARD - 1/4 WAVE, 400 - 512 MHz, TNC COVERED, 6"	60%	US
Hutton	132-8	Larsen	SPWH20420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, SMA M T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH20450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, SMA M T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH20470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, SMA M T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH20490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, SMA M T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH20832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, SMA M T1, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPWH20918	WHIP - STANDARD - 1/4 WAVE, 863 - 973 MHz, SMA M T1, 2 3/4"	60%	US
Hutton	132-8	Larsen	SPWH20FT	WHIP - STANDARD - 1/4 WAVE, 400 - 512 MHz, SMA M T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH21420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, SMA F T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH21450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, SMA F T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH21470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, SMA F T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH21490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, SMA F T1, 6"	60%	US
Hutton	132-8	Larsen	SPWH21832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, SMA F T1, 3"	60%	US
Hutton	132-8	Larsen	SPWH21918	WHIP - STANDARD - 1/4 WAVE, 863 - 973 MHz, SMA F T1, 3"	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	SPWH21FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, SMA F T1	60%	US
Hutton	132-8	Larsen	SPWH22420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, SMA F T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH22450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, SMA F T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH22470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, SMA F T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH22490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, SMA F T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH22832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, SMA F T2, 3"	60%	US
Hutton	132-8	Larsen	SPWH22918	WHIP - STANDARD - 1/4 WAVE, 863 - 973 MHz, SMA F T2, 3"	60%	US
Hutton	132-8	Larsen	SPWH22FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, SMA F T2, 7"	60%	US
Hutton	132-8	Larsen	SPWH23420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, SMA F T3, 6"	60%	US
Hutton	132-8	Larsen	SPWH23450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, SMA F T3, 6"	60%	US
Hutton	132-8	Larsen	SPWH23470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, SMA F T3, 6"	60%	US
Hutton	132-8	Larsen	SPWH23490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, SMA F T3, 6"	60%	US
Hutton	132-8	Larsen	SPWH23832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, SMA F T3, 3"	60%	US
Hutton	132-8	Larsen	SPWH23918	WHIP - STANDARD - 1/4 WAVE, 863 - 973 MHz, SMA F T3, 3"	60%	US
Hutton	132-8	Larsen	SPWH23FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, SMA F T3, 6"	60%	US
Hutton	132-8	Larsen	SPWH24420	WHIP - STANDARD - 1/4 WAVE, 395 - 445 MHz, SMA M T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH24450	WHIP - STANDARD - 1/4 WAVE, 425 - 475 MHz, SMA M T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH24470	WHIP - STANDARD - 1/4 WAVE, 450 - 480 MHz, SMA M T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH24490	WHIP - STANDARD - 1/4 WAVE, 470 - 512 MHz, SMA M T2, 6"	60%	US
Hutton	132-8	Larsen	SPWH24832	WHIP - STANDARD - 1/4 WAVE, 872 - 882 MHz, SMA M T2, 3"	60%	US
Hutton	132-8	Larsen	SPWH24918	WHIP - STANDARD - 1/4 WAVE, 863 - 973 MHz, SMA M T2, 3"	60%	US
Hutton	132-8	Larsen	SPWH24FT	WHIP - STANDARD - 1/4 WAVE, FIELD TUNABLE, 400 - 512 MHz, SMA M T2, 7"	60%	US
Hutton	132-8	Larsen	SW24008	WALL-MOUNTED DIRECTIONAL PATCH, 8.5 dBi, 2400 - 2500 MHz, SMA R/A	60%	US
Hutton	132-8	Larsen	TLM34	CHROME TLM 3/4" MOUNT	60%	US
Hutton	132-8	Larsen	TMB34	CHROME TMB 3/4" MOUNT	60%	US
Hutton	132-8	Larsen	TMB34B	TMB 3/4" MOUNT	60%	US
Hutton	132-8	Larsen	TMB34D	CHROME TMB 3/4" MOUNT FOR DODGE TRUCK	60%	US
Hutton	132-8	Larsen	TMB38	CHROME TMB 3/8" MOUNT	60%	US
Hutton	132-8	Larsen	TMB38/34	MIRROR MOUNT BRACKET 3/8" X, 3/4"	60%	US
Hutton	132-8	Larsen	TMB38/50	CHROME TMB 3/8" MOUNT, NO SCREWS, BULK PACK (50/PACK)	60%	US
Hutton	132-8	Larsen	TMB38B	TMB 3/8" MOUNT	60%	US
Hutton	132-8	Larsen	TMB58	CHROME TMB 5/8" MOUNT	60%	US
Hutton	132-8	Larsen	TMB58B	TMB 5/8" MOUNT	60%	US
Hutton	132-8	Larsen	TMBGPS	GPS TRUNK MOUNT BRACKET KT	60%	US
Hutton	132-8	Larsen	TMBOM	OM CHROME TMB BRACKET	60%	US
Hutton	132-8	Larsen	TNC	CONNECTOR, MALE SOLDER, RG-58	60%	US
Hutton	132-8	Larsen	TNC174	CONNECTOR, MALE SOLDER, RG-174	60%	US
Hutton	132-8	Larsen	TNCAP	CONNECTOR, B1264TNC ANGLE PLUG, 58/U	60%	US
Hutton	132-8	Larsen	TNCAP/J	CONNECTOR, TNC ANGLE ADAPTER, P/J	60%	US
Hutton	132-8	Larsen	TNCCBJ	CONNECTOR, TNC CRIMP B JACK, 58/U	60%	US
Hutton	132-8	Larsen	TNCCJ	CONNECTOR, TNC CRIMP JACK, 58/U	60%	US
Hutton	132-8	Larsen	TNCCRIMP	CONNECTOR, TNC CRIMP MALE, RG-58	60%	US
Hutton	132-8	Larsen	TNCCRIMP25	PKG OF 25, TNC CRIMP CONNECTORS, MALE, RG-58	60%	US
Hutton	132-8	Larsen	TNCQ	1/4 WAVE ANTENNA (136 - 512 MHz) FOR TNC MOUNT	60%	US
Hutton	132-8	Larsen	UD1000	1000' ROLL OF RG58/U DUAL SHIELD COAX	60%	US
Hutton	132-8	Larsen	UD1000	1000' ROLL OF RG58/U DUAL SHIELD COAX	60%	US
Hutton	132-8	Larsen	UDCOAX	CABLE, UD RG-58/U, SOLID CENTER, POLYETHYLENE DIELECTRIC	60%	US
Hutton	132-8	Larsen	UG175	REDUCING ADAPTOR FOR PL259	60%	US
Hutton	132-8	Larsen	UHFBJJ	UHF BULKHEAD	60%	US
Hutton	132-8	Larsen	W030	WHIP FOR 1/4 WAVE ANTENNA (806 - 866 MHz)	60%	US
Hutton	132-8	Larsen	W030B	BLACK WHIP FOR 1/4 WAVE ANTENNA (806 - 866 MHz)	60%	US
Hutton	132-8	Larsen	W035	WHIP FOR 1/4 WAVE ANTENNA (902 - 928 MHz)	60%	US
Hutton	132-8	Larsen	W035B	BLACK WHIP FOR 1/4 WAVE ANTENNA (902 - 928 MHz)	60%	US
Hutton	132-8	Larsen	W142B	WHIP, 5/8 OVER 1/4, 406 - 420 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W143B	WHIP, 5/8 OVER 1/4, 420 - 440 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W144B	WHIP, 5/8 OVER 1/4, 440 - 460 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W145B	WHIP, 5/8 OVER 1/4, 450 - 470 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W146B	WHIP, 5/8 OVER 1/4, 470 - 490 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W147B	WHIP, 5/8 OVER 1/4, 490 - 512 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W150/450	WHIP, 150 - 154 / 450 - 460 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W152	WHIP, 5/8 OVER 1/2 ENCLOSED, 406 - 420 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W153	WHIP, 5/8 OVER 1/2 ENCLOSED, 420 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W154	WHIP, 5/8 OVER 1/2 ENCLOSED, 440 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W155	WHIP, 5/8 OVER 1/2 ENCLOSED, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W156	WHIP, 5/8 OVER 1/2 ENCLOSED, 470 - 490 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W157	WHIP, 5/8 OVER 1/2 ENCLOSED, 490 - 512 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W158	WHIP, 5/8 OVER 5/8 ENCLOSED, 406 - 420 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W159	WHIP, 5/8 OVER 5/8 ENCLOSED, 420 - 440 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W160	WHIP, 5/8 OVER 5/8 ENCLOSED, 440 - 460 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W161	WHIP, 5/8 OVER 5/8 ENCLOSED, 450 - 470 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W162	WHIP, 5/8 OVER 5/8 ENCLOSED, 470 - 490 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W163	WHIP, 5/8 OVER 5/8 ENCLOSED, 490 - 512 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W170	WHIP, 1/2 WAVE, 406 - 512 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W170B	WHIP, 1/2 WAVE, 406 - 512 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W180	WHIP WITH CHROME SPRING FOR NMO700	60%	US
Hutton	132-8	Larsen	W180	WHIP WITH CHROME SPRING FOR NMO700	60%	US
Hutton	132-8	Larsen	W185	WHIP WITH CHROME SPRING FOR NMO825	60%	US
Hutton	132-8	Larsen	W185	WHIP WITH CHROME SPRING FOR NMO825	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	W190	WHIP, WITH SPRING FOR NMO800	60%	US
Hutton	132-8	Larsen	W190B	WHIP, WITH BLACK SPRING FOR NMO800B	60%	US
Hutton	132-8	Larsen	W195	CHROME SPRING NMO WHIP, ENCLOSED, 890 - 960 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W195B	WHIP WITH BLACK SPRING FOR NMO900B	60%	US
Hutton	132-8	Larsen	W270	WHIP, 144 - 148 / 442 - 448 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W270B	WHIP, 144 - 148 / 442 - 448 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W200	WHIP, 1/4 WAVE, 136 - 960 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W200B	WHIP, 1/4 WAVE, 136 - 960 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	W320B	BLACK WHIP FOR 200 - 265 MHz	60%	US
Hutton	132-8	Larsen	W490	WHIP, 1/4 WAVE, 88 - 265 MHz, .100 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	W400B	WHIP, 1/4 WAVE, 88 - 265 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	W490	WHIP, 5/8 WAVE, 27 - 174 MHz, .100 DIA CHROME WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490	WHIP, 5/8 WAVE, 27 - 174 MHz, .100 DIA CHROME WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490.125	WHIP, 5/8 WAVE, 27-174 MHz, .125 DIA CHROME WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490.125	WHIP, 5/8 WAVE, 27-174 MHz, .125 DIA CHROME WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490.125B	WHIP, 5/8 WAVE, 27 - 174 MHz, .125 DIA WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490.125U	WHIP, 5/8 WAVE, 27 - 174 MHz, .125 DIA UNPLATED WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490B	WHIP, 5/8 WAVE, 27 - 174 MHz, .100 DIA WHIP, 49"	60%	US
Hutton	132-8	Larsen	W490U	WHIP, 5/8 WAVE, 27 - 174 MHz, .100 DIA UNPLATED WHIP, 49"	60%	US
Hutton	132-8	Larsen	W540	WHIP, 5/8 OR 1/4 WAVE, 27 - 174 MHz, .100 DIA CHROME WHIP, 54"	60%	US
Hutton	132-8	Larsen	W540.125	WHIP, 5/8 OR 1/4 WAVE, 27 - 174 MHz, .125 DIA CHROME WHIP, 54"	60%	US
Hutton	132-8	Larsen	W540.125B	WHIP, 5/8 OR 1/4 WAVE, 27 - 174 MHz, .125 DIA WHIP, 54"	60%	US
Hutton	132-8	Larsen	W540B	WHIP, 5/8 OR 1/4 WAVE, 27 - 174 MHz, .100 DIA WHIP, 54"	60%	US
Hutton	132-8	Larsen	W640	WHIP, 5/8 OR 1/4 WAVE, 27 - 174 MHz, .100 DIA CHROME WHIP, 64"	60%	US
Hutton	132-8	Larsen	W640B	WHIP, 5/8 OR 1/4 WAVE, 27 - 174 MHz, .100 DIA WHIP, 64"	60%	US
Hutton	132-8	Larsen	WCM825B	CM WHIP, 3 dB, 825 - 896 MHz	60%	US
Hutton	132-8	Larsen	WCP3E	WHIP ENCLOSED, 3 dB, 824 MHz / 1850 MHz FOR KG, MM, NMO	60%	US
Hutton	132-8	Larsen	WCP3U	WHIP ENCLOSED, UNITY, 3 dB, 824 MHz / 1850 MHz FOR KG, MM, NMO	60%	US
Hutton	132-8	Larsen	WGPSCW150	1/4 WAVE - VHF 136 WHIP	60%	US
Hutton	132-8	Larsen	WGPSCW220	1/4 WAVE - VHF 218 WHIP	60%	US
Hutton	132-8	Larsen	WGPSCW3E800	5 dBi WHIP	60%	US
Hutton	132-8	Larsen	WGPSCW3E900	5 dBi WHIP	60%	US
Hutton	132-8	Larsen	WGPSCW450	1/4 WAVE - UHF WHIP	60%	US
Hutton	132-8	Larsen	WGPSCW800	1/4 WAVE - 800 WHIP	60%	US
Hutton	132-8	Larsen	WGPSCW900	1/4 WAVE - 900 WHIP	60%	US
Hutton	132-8	Larsen	WKD142MHW	WHIP FOR KD142MHW	60%	US
Hutton	132-8	Larsen	WKG144	KG WHIP, 144 - 160 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG160	KG WHIP, 160 - 174 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG270	KG WHIP, 144 - 148 MHz / 440 - 450MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG220	KG WHIP, 3 dB, 220 - 225 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG3825	KG WHIP, 3 dB, 825 - 896 MHz	60%	US
Hutton	132-8	Larsen	WKG3900	KG WHIP, 3 dB, 865 - 970 MHz	60%	US
Hutton	132-8	Larsen	WKG3E825	KG WHIP ENCLOSED, 3 dB, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	WKG3E900	KG WHIP ENCLOSED, 3 dB, 865 - 965 MHz	60%	US
Hutton	132-8	Larsen	WKG406	KG WHIP, 406 - 420 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG440	KG WHIP, 440 - 450 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG450	KG WHIP, 450 - 470 MHz, .100 DIA WHIP	60%	US
Hutton	132-8	Larsen	WKG5E900	KG WHIP, ENCLOSED, 5 dB, 865 - 965 MHz	60%	US
Hutton	132-8	Larsen	WKGU825	KG WHIP, UNITY, 806 - 896 MHz	60%	US
Hutton	132-8	Larsen	WLAWBQ	LAWBQ WHIP, UNITY, 150 - 170 MHz, .125 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	WNMO3E700B	REPLACEMENT WHIP FOR NMO3E700B	60%	US
Hutton	132-8	Larsen	WNMO3E700B	REPLACEMENT WHIP FOR NMO3E700B	60%	US
Hutton	132-8	Larsen	WNMO3E800B	REPLACEMENT WHIP FOR NMO3E800B	60%	US
Hutton	132-8	Larsen	WNMO3E825B	REPLACEMENT WHIP FOR NMO3E825B	60%	US
Hutton	132-8	Larsen	WNMO3E900B	REPLACEMENT WHIP FOR NMO3E900B	60%	US
Hutton	132-8	Larsen	WNMO5T800B	REPLACEMENT WHIP FOR NMO5T800B	60%	US
Hutton	132-8	Larsen	WNMO5T825B	REPLACEMENT WHIP FOR NMO5T825B	60%	US
Hutton	132-8	Larsen	WNMO5T900B	REPLACEMENT WHIP FOR NMO5T900B	60%	US
Hutton	132-8	Larsen	WNMOQSPEC	CHROME NMOQ, SPEC WHIP, UNITY, 136 - 512 MHz, WITH GASKET AND PIN	60%	US
Hutton	132-8	Larsen	WNMOQSPEC825	WHIP FOR NMOQ, SPEC825	60%	US
Hutton	132-8	Larsen	WNMOQSPEC825B	BLACK WHIP FOR NMOQ, SPEC825B	60%	US
Hutton	132-8	Larsen	WNMOQSPEC900	WHIP FOR NMOQ, SPEC900	60%	US
Hutton	132-8	Larsen	WNMOQSPEC900B	BLACK WHIP FOR NMOQ, SPEC900B	60%	US
Hutton	132-8	Larsen	WNMOQSPECB	NMOQ, SPEC WHIP, UNITY, 136 - 512 MHz, WITH GASKET AND PIN	60%	US
Hutton	132-8	Larsen	WNMOSPEC800	CHROME NMO, SPEC WHIP, 3 dB, 806 - 866 MHz, .070 DIA CHROME WHIP	60%	US
Hutton	132-8	Larsen	WNMOSPEC800B	NMO, SPEC WHIP, 3 dB, 806 - 866 MHz, .070 DIA WHIP	60%	US
Hutton	132-8	Larsen	WNMOSPEC825	CHROME NMO, SPEC WHIP, 3 dB, 825 - 896 MHz	60%	US
Hutton	132-8	Larsen	WNMOSPEC825B	NMO, SPEC WHIP, 3 dB, 825 - 896 MHz	60%	US
Hutton	132-8	Larsen	WNMOSPEC900	CHROME NMO, SPEC WHIP, 3 dB, 890 - 960 MHz	60%	US
Hutton	132-8	Larsen	WNMOSPEC900B	NMO, SPEC WHIP, 3 dB, 890 - 960 MHz	60%	US
Hutton	132-8	Larsen	WNMOWB406C	WIDEBAND CHROME WHIP WITH SPRING, 406 - 430 MHz,	60%	US
Hutton	132-8	Larsen	WNMOWB430C	WIDEBAND CHROME WHIP WITH SPRING, 430 - 455 MHz,	60%	US
Hutton	132-8	Larsen	WNMOWB450C	WIDEBAND CHROME WHIP WITH SPRING, 450 - 475 MHz,	60%	US
Hutton	132-8	Larsen	WNMOWB470C	WIDEBAND CHROME WHIP WITH SPRING, 470 - 495 MHz,	60%	US
Hutton	132-8	Larsen	WNMOWB490C	WIDEBAND CHROME WHIP WITH SPRING, 490 - 515 MHz,	60%	US
Hutton	132-8	Larsen	WNMOWBQ	NMO WBQ CHROME WHIP, UNITY 150 - 170 MHz	60%	US
Hutton	132-8	Larsen	WNMOWBQB	NMO WBQ WHIP, UNITY, 150 - 170 MHz	60%	US
Hutton	132-8	Larsen	WOM825	WHIP FOR OM825	60%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	WPHW	WHIP FOR PHW150 & PHW220	60%	US
Hutton	132-8	Larsen	YA3406N	YAGI, 5 ELEM, 11.2 dBi, 406 - 430 MHz, N FEMALE, STAKED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3406PL	YAGI, 5 ELEM, 11.2 dBi, 406 - 430 MHz, UHF, STAKED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3406WN	YAGI, 5 ELEM, 11.2 dBi, 406 - 430 MHz, N FEMALE, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3406WPL	YAGI, 5 ELEM, 11.2 dBi, 406 - 430 MHz, UHF, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3450N	YAGI, 5 ELEM, 11.2 dBi, 440 - 470 MHz, N FEMALE, STAKED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3450PL	YAGI, 5 ELEM, 11.2 dBi, 440 - 470 MHz, UHF, STAKED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3450WN	YAGI, WELDED 5 ELEM, 11.2 dBi, 440 - 470 MHz, N FEMALE,	60%	US
Hutton	132-8	Larsen	YA3450WPL	YAGI, WELDED 5 ELEM, 11.2 dBi, 440 - 470 MHz, UHF, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3470N	YAGI, 5 ELEM, 11.2 dBi, 470 - 512 MHz, N FEMALE, STAKED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3470WN	YAGI, 5 ELEM, 11.2 dBi, 470 - 490 MHz, N FEMALE, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3490N	YAGI, 5 ELEM, 11.2 dBi, 490 - 512 MHz, N FEMALE, STAKED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA3490WN	YAGI, 5 ELEM, 11.2 dBi, 490 - 512 MHz, N FEMALE, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5740W	YAGI, 7 ELEMENT, 11 dBi, 740 - 806 MHz, N FEMALE CONNECTOR, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5740W	YAGI, 7 ELEMENT, 11 dBi, 740 - 806 MHz, N FEMALE CONNECTOR, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5800W	YAGI, 7 ELEM, 11 dBi, 806 - 866 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5800W	YAGI, 7 ELEM, 11 dBi, 806 - 866 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5825W	YAGI, 7 ELEM, 11 dBi, 824 - 896 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5825W	YAGI, 7 ELEM, 11 dBi, 824 - 896 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5900W	YAGI, 7 ELEM, 11 dBi, 890 - 960 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA5900W	YAGI, 7 ELEM, 11 dBi, 890 - 960 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6740W	YAGI, 4 ELEMENT, 8 dBi, 740 - 806 MHz, N FEMALE CONNECTOR, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6740W	YAGI, 4 ELEMENT, 8 dBi, 740 - 806 MHz, N FEMALE CONNECTOR, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6800W	YAGI, 4 ELEM, 8 dBi, 806 - 866 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6800W	YAGI, 4 ELEM, 8 dBi, 806 - 866 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6825W	YAGI, 4 ELEM, 8 dBi, 824 - 896 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6825W	YAGI, 4 ELEM, 8 dBi, 824 - 896 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6900W	YAGI, 4 ELEM, 8 dBi, 890 - 960 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YA6900W	YAGI, 4 ELEM, 8 dBi, 890 - 960 MHz, N FEMALE CONN, WELDED ELEMENTS	60%	US
Hutton	132-8	Larsen	YAGI3KITS	MOUNT BRACKET FOR YA3, YA5, YA6	60%	US
Hutton	132-8	Larsen	GPSCP01	WHITE TRIBAND PIFA EXTERIOR MOUNT, 824 / 1850 / 1575 MHz, NO CONN	59%	US
Hutton	132-8	Larsen	GPSCP02	BLACK TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, NO CONN / SMA	59%	US
Hutton	132-8	Larsen	GPSCP03	WHITE TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, NO CONN / SMA	59%	US
Hutton	132-8	Larsen	GPSCP04	BLACK TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, NO CONN / SMB	59%	US
Hutton	132-8	Larsen	GPSCP05	WHITE TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, NO CONN / SMB	59%	US
Hutton	132-8	Larsen	GPSCP06	BLACK TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, SMA / SMA	59%	US
Hutton	132-8	Larsen	GPSCP07	WHITE TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, SMA / SMA	59%	US
Hutton	132-8	Larsen	GPSCP08	BLACK TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, MPL / SMA	59%	US
Hutton	132-8	Larsen	GPSCP09	WHITE TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, MPL / SMA	59%	US
Hutton	132-8	Larsen	GPSCP10	BLACK TRIBAND PIFA, EXTERIOR MOUNT, 824 / 1850 / 1575, TNC / BNC	59%	US
Hutton	132-8	Larsen	GPSCPC01	TRIBAND INTERIOR CARD, 16' RG-58 / 16' RG-174, NO CONN / SMA	59%	US
Hutton	132-8	Larsen	GPSCPC02	TRIBAND INTERIOR CARD, 16' RG-58 / 16' RG-174, NO CONN / SME	59%	US
Hutton	132-8	Larsen	GPSCPGM01	INT GLASS MOUNT CELL / PCS / GPS, 16' RG-174, NO CONN / SMA	59%	US
Hutton	132-8	Larsen	GPSCPGM02	INT GLASS MOUNT CELL / PCS / GPS, 16' RG-174, NO CONN / SMB	59%	US
Hutton	132-8	Larsen	GPSCPGM03	INT GLASS MOUNT, 1575.42 / 824-894 / 1850-1990 MHz, 16' RG-174, SMA / MPL	59%	US
Hutton	132-8	Larsen	GPSCPGM04	INT GLASS MOUNT CELL / PCS / GPS, 16' RG-174, SMA / SMA	59%	US
Hutton	132-8	Larsen	GPSCW1503	GPSCW, UNITY, 136 - 174 / 1575.5 MHz, 16' 4" RG-174, SMA (GPS) / FME (VHF)	59%	US
Hutton	132-8	Larsen	GPSCW3E8003	GPSCW ENC, 3 dB, 806 - 896 / 1575.4 MHz, 16' 4" RG-174, FME (GPS) / SMA (CELL)	59%	US
Hutton	132-8	Larsen	GPSCW3E8004	GPSCW ENC, 3 dB, 806 - 896 / 1575.4 MHz, 16' 4" RG-174, SMA (GPS) / TNC (CELL)	59%	US
Hutton	132-8	Larsen	GPSCWCP01	ROOF MOUNT TRI BAND, 824 - 894 MHz / 1850 - 1990 MHz / 1575.42 MHz, 16' RG-74 / 16' RG-174, NO CONN / SMA	59%	US
Hutton	132-8	Larsen	GPSCWCP02	ROOF MOUNT TRI BAND, 824 - 894 MHz / 1850 - 1990 MHz / 1575.42 MHz, 16' RG-74 / 16' RG-174, NO CONN / SMB	59%	US
Hutton	132-8	Larsen	GPSCWCP03	ROOF MOUNT TRI BAND, 824 - 894 MHz / 1850 - 1990 MHz / 1575.42 MHz, 16' RG-74 / 16' RG-174, SMA / MPL	59%	US
Hutton	132-8	Larsen	GPSCWCP04	ROOF MOUNT TRI BAND, 824 - 894 MHz / 1850 - 1990 MHz / 1575.42 MHz, 16' RG-74 / 16' RG-174, SMA / SMA	59%	US
Hutton	132-8	Larsen	GPSDM11	WHITE GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, NO CONN	59%	US
Hutton	132-8	Larsen	GPSDM12	BLACK GPS DIRECT MOUNT, 1575.4 MHz, 17' RG-174, NO CONN	59%	US
Hutton	132-8	Larsen	GPSGM12	GPS GLASS MOUNT, 1575.4 MHz, 17' RG-174, NO CONN	59%	US
Hutton	132-8	Larsen	KG144UDFME	ON GLASS, 2 dBi, 144 - 160 MHz, 14' UD, FME CRIMP	59%	US
Hutton	132-8	Larsen	KG450DUD	ON GLASS, DISGUISE, UNITY, 450 - 470 MHz, 14' UD, PL259T	59%	US
Hutton	132-8	Larsen	KG450UDMPL	ON GLASS, 2.5 dB, 450 - 470 MHz, 14' UD, MPL	59%	US
Hutton	132-8	Larsen	LPT2400NMOHFUD	NMOHF TRANSIT ANTENNA WITH MOUNT, 2 dBi, 2.4 - 2.5 GHz	59%	US
Hutton	132-8	Larsen	LPT825/19NMOSMA	TRANSIT ANTENNA WITH NMOKHFUDSMA	59%	US
Hutton	132-8	Larsen	MMS5E900BNC	MAG MOUNT, 5 dB, 890 - 960 MHz, BNC CRIMP	59%	US
Hutton	132-8	Larsen	NMO150CHFUD10	NMO150C, NMOKHFUD, NO CONN, 10 EACH PER PACK	59%	US
Hutton	132-8	Larsen	NMO3E800BHFUD10	NMO3E800B, NMOKHFUD NO CONN, 10 EACH PER PACK	59%	US
Hutton	132-8	Larsen	NMO450CHFUD10	NMO450C, NMOKHFUD NO CONN, 10 EACH PER PACK	59%	US
Hutton	132-8	Larsen	NMO4E4900B	NMOHF ENC COIL WHIP, 4 dBi, 4900 - 5350 MHz	59%	US
Hutton	132-8	Larsen	NMO4E4900BK	NMOHF ENC COIL WHIP, 4 dBi, 4900 - 5350 MHz, 12' SHF-142 (RG-58U TYPE), NO CONN	59%	US
Hutton	132-8	Larsen	NMO4E5740B	NMOHF ENC COIL WHIP, 4 dBi, 5470 - 5900 MHz	59%	US
Hutton	132-8	Larsen	NMO4E5740BK	NMOHF ENC COIL WHIP, 4 dBi, 5470 - 5900 MHz, 12' SHF-142 (RG-58U TYPE), NO CONN	59%	US
Hutton	132-8	Larsen	NMOC/P3E	BASE WHIP ENCLOSED, 4 dBi, 806 - 896 MHz / 1850 - 1990 MHz	59%	US
Hutton	132-8	Larsen	NMOC/P3EUD	BASE WHIP ENC, 4 dBi, 806 - 896 MHz / 1850 - 1990 MHz, 17' UD, NO CONN, ENC NMO MOUNT	59%	US
Hutton	132-8	Larsen	NMOC/P3EUDFME	BASE WHIP ENC, 4 dBi, 806 - 896 MHz / 1850 - 1990 MHz, 17' UD, FME INSTALLED, ENC NMO MOUNT	59%	US

**Hutton Communications, Inc.**  
2006 GSA Pricelist

Dealer	SIN	Mfr Name	Mfr Part Number	Product Description	GSA Discount	Prod Point
Hutton	132-8	Larsen	NMOC/P3EUDMPL	BASE WHIP ENC, 4 dBi, 806 - 896 MHz / 1850 - 1990 MHz, 17' UD, MPL, ENCLOSED NMO MOUNT	59%	US
Hutton	132-8	Larsen	NMOC/P3EUDSMA	BASE WHIP ENC, 4 dBi, 806 - 896 MHz / 1850 - 1990 MHz, 17' UD, SMA Male, ENCLOSED NMO MOUNT	59%	US
Hutton	132-8	Larsen	NMOC/P3EUDTNC	BASE WHIP ENCLOSED, 4 dBi, 806 - 896 MHz / 1850 - 1990 MHz, 17' UD, TNC, ENC NMO MOUNT	59%	US
Hutton	132-8	Larsen	NMOHFTHK	NMO HF THICK MOUNT, 1/2" THICK SURFACE, NO CABLE	59%	US
Hutton	132-8	Larsen	NMOK25	NMO MOUNT, 25' CX, PL259	59%	US
Hutton	132-8	Larsen	NMOK25NOCNN	NMO MOUNT, 25' CX, NO CONN	59%	US
Hutton	132-8	Larsen	NMOKDS22MPLI	NMO MOUNT, 22' DS, MPL CRIMP	59%	US
Hutton	132-8	Larsen	NMOKHFCXTHK	NMO HF THICK MOUNT, 1/2" THICK SURFACE, 17' CX, NO CONN	59%	US
Hutton	132-8	Larsen	NMOKHFDSTHK	NMO HF THICK MOUNT, 1/2" THICK SURFACE, 17' DS, NO CONN	59%	US
Hutton	132-8	Larsen	NMOKHFUD35	NMOKHFUD WITH 35' OF COAX	59%	US
Hutton	132-8	Larsen	NMOKHFUDPL	NMO HGH FREQUENCY MOUNT, 17' RG-58UD, PL259T	59%	US
Hutton	132-8	Larsen	NMOKHFUDTHK	NMO HF THICK MOUNT, 1/2" THICK SURFACE, 17' UD, NO CONN	59%	US
Hutton	132-8	Larsen	NMOKUD25MPL	NMO MOUNT, 25' UD, MPL CRIMP	59%	US
Hutton	132-8	Larsen	NMOKUD25MPL	NMO MOUNT, 25' UD, MPL CRIMP	59%	US
Hutton	132-8	Larsen	NMOKUDSMA	NMO MOUNT, 17' UD COAX, SMA MALE PACKAGED NOT INSTALLED	59%	US
Hutton	132-8	Larsen	NMOKUDSMAI	NMO MOUNT, 17' UD, SMA MALE	59%	US
Hutton	132-8	Larsen	NMOMMRDSSMA	NMO 3.5" ROUND MAG MOUNT, 12' DS, SMA CRIMP	59%	US
Hutton	132-8	Larsen	NMOMMRUD25NC	NMO 3.5" ROUND MAG MOUNT, 25' UD, NO CONN	59%	US
Hutton	132-8	Larsen	PL25925	PL259, 25 PER PACK	59%	US
Hutton	132-8	Larsen	PL259T25	PL259T, 25 PER PACK	59%	US
Hutton	132-8	Larsen	R380.500.220	RADOME OMNI, 8 dBi, 2400 - 2500 MHz, N FEMALE	59%	US
Hutton	132-8	Larsen	R380.500.222	PLANAR ARRAY, VERT POLARIZATION, 21 dBi, 4940-4990 MHz, 8" SHF-142, N	59%	US
Hutton	132-8	Larsen	R380.500.223	RADOME OMNI, 11 dBi, 4940 - 4900 MHz, N FEMALE	59%	US
Hutton	132-8	Larsen	R380.500.314	SWIVEL MOUNT DIPOLE, 1.6 dBi/5 dBi MAX GAIN, 2400 - 2500 MHz / 4900 - 5900 MHz, RPTNC	59%	US
Hutton	132-8	Larsen	R380.500.901	BI-DIRECTIONAL CEILING MOUNT, 3.5 dBi, 2400 - 2500 MHz, 2' RG-58 A/U (WHITE), SMA JACK (FEMALE)	59%	US
Hutton	132-8	Larsen	R380.900.500	OMNI CEILING DUAL BAND , 2 dBi, 2400 - 2500 MHz / 4900 - 5900 MHz, 12" RG-58 A/U (WHITE), N FEMALE	59%	US
Hutton	132-8	Larsen	R380.900.903	CEILING, 4.2 dBi, 5150 - 5875 MHz, 12" RG-58 A/U (WHITE), N	59%	US
Hutton	132-8	Larsen	R380.900.904	MAST/WALL MOUNT DIRECTIONAL PATCH, 9.4 dBi, 5150 - 5875 MHz, 2' RG-58 A/U (WHITE), SMA JACK (FEMALE)	59%	US
Hutton	132-8	Larsen	R380.900.908	BI-DIRECTIONAL DUAL BAND , 4.5 dBi/5 dBi, 2400-2500 MHz/4900-5900 MHz, 2' RG-58 A/U (WHITE), SMA JACK (FEMALE)	59%	US
Hutton	132-8	Larsen	R380.900.909	MAST/WALL MOUNT DIRECTIONAL PATCH, DUAL BAND, 5.5 dBi/9 dBi, 2400-2500 MHz/4.9-5.9 GHz, 3' RG-58 A/U (W), RPTNC PLUG (M)	59%	US
Hutton	132-8	Larsen	R380.900.910	CEILING QUAD BAND, 2 dBi, 806 - 960 MHz / 1710 - 1990 MHz, 12" RG-58 A/U (WHITE), N FEMALE	59%	US
Hutton	132-8	Larsen	SB800SMA12	STEALTH BLADE, 806 - 896 MHz, 12' RG-174, SMA MALE	59%	US
Hutton	132-8	Larsen	SB800SMA3	STEALTH BLADE, 806 - 896 MHz, 3' RG-174, SMA	59%	US
Hutton	132-8	Larsen	SPWB21150	WHIP - STANDARD - 1/4 WAVE, 136 - 174 MHz, SMA F T1, 6.7'	59%	US
Hutton	132-8	Larsen	SPWB22150	WHIP - STANDARD - 1/4 WAVE, 136 - 174 MHz, SMA F T2, 6.7'	59%	US
Hutton	132-8	Larsen	TMB14	TMB 1/4" MOUNT	59%	US
Hutton	132-8	Larsen	W155B	WHIP, 5/8 OVER 1/2 ENCLOSED, 450 - 470 MHz, .100 DIA BLACK WHIP	59%	US
Hutton	132-8	Larsen	W218	WHIP, 1/2 WAVE, 218 MHz, .100 DIA CHROME WHIF	59%	US
Hutton	132-8	Larsen	W218B	WHIP, 1/2 WAVE, 218 MHz, .100 DIA BLACK WHIP	59%	US
Hutton	132-8	Larsen	PA18902N	PANEL, 8 dBi, 890 - 960 MHz, N CONN, SINGLE ELEMENT	59%	US
Hutton	132-8	Larsen	POMMRPL	PO ROUND MAG MOUNT, 12' CX, PL259	59%	US
Hutton	132-8	Larsen	MSC/P3USMA	2" MAG MOUNT / WHIP, UNITY / 3 dB, 824 / 1850 MHz, 12' DS, SMA	59%	US
Hutton	132-8	Larsen	MMC/P3ESMA	MAG MOUNT / WHIP ENC, 3 dB, 825 - 896 / 850 - 1990 MHz, 12' DS, SMA	59%	US
Hutton	132-8	Larsen	NMOQW152CXPL10	NMO MAG MOUNT, 12' CX, TNC CRIMP, 10 PER PACK	59%	US
Hutton	132-8	Larsen	MM5T900SMARP	MAG MOUNT, 5 dB, 890 - 960 MHz, 12' DS, SMA	59%	US
Hutton	132-8	Larsen	MM3E900SMA	3" MAG MOUNT / WHIP ENCLOSED, 3 dB, 890 - 960 MHz, 12' DS, SMA	59%	US
Hutton	132-8	Larsen	MS3E800SMA	2" MAG MOUNT / WHIP ENCLOSED, 3 dB, 806 - 896 MHz, 12' RG-174, SMA	59%	US
Hutton	132-8	Larsen	LP800SMA	LOW PROFILE, UNITY, 806 - 960 MHz, 17' UD, SMA CP 58	59%	US
Hutton	132-8	Larsen	SB450MPL12	STEALTH BLADE, 450 - 470 MHz, 12' RG-316, MPL	59%	US
Hutton	132-8	Larsen	KG825UDN	ON GLASS, 3 dB, 806 - 896 MHz, 14' UD, N	60%	US
Hutton	132-8	Larsen	MM5T900SMA	MAG MOUNT / WHIP, 5 dB, 890 - 960 MHz, 12' DS, SMA RP	59%	US
Hutton	132-8	Larsen	NMO462HWBES	HW COIL / WHIP, 5.5 dBi, 462 MHz, BLACK WHIP, SPRING B	59%	US
Hutton	132-8	Larsen	NMOKHFUD25	NMOKHFUD WITH 25' OF COAX	59%	US
Hutton	132-8	Larsen	NMOKUDPL25	NMO MOUNT, 25' UD, PL259	59%	US
Hutton	132-8	Larsen	LMK1/4"	LM MOUNT, 1/4" LONGER STUD, 17' CX, PL259	60%	US