



N Male  
L4PNM-RC



N Female  
L4PNF-RC



7-16 DIN Male  
L4PDM-RC



7-16 DIN Female  
L4PDF-RC



7/8" EIA Flange  
L44R



UHF Male  
L44P

## Connectors

Interface	Description	Type Number	Inner Contact Attachment	Outer Contact Attachment	Plating Code	Max. Length in (mm)	Max. Dia. in (mm)
N Male	Hex Head	<b>L4PNM-H</b>	Solder	Self-Flare	SG	2.6 (66)	0.95 (24.1)
N Male	RingFlare	<b>L4PNM-RC</b>	Captivated	RingFlare	SG	3.0 (75.7)	0.86 (21.8)
N Male	Right Angle, Hex	<b>L4PNR-H</b>	Solder	Self-Flare	SG	3.2/1.5 (81/38)	0.95 (24.1)
N Male	Right Angle, Hex	<b>L4PNR-HC</b>	Captivated	Self-Flare	SG	3.2/1.5 (81/38)	0.91 (23.1)
N Female	–	<b>L4PNF</b>	Solder	Self-Flare	SG	2.6 (66)	0.94 (23.9)
N Female	Bulk Head	<b>L4PNF-BH</b>	Solder	Self-Flare	SG	2.6 (66)	0.96 (24.4)
N Female	Panel Mount	<b>L4PNF-PM</b>	Solder	Self-Flare	SG	2.6 (66)	1.0 (25.4)
N Female	RingFlare	<b>L4PNF-RC</b>	Captivated	RingFlare	SG	2.8 (71)	0.86 (21.8)
7-16 DIN Male	–	<b>L4PDM</b>	Solder	Self-Flare	SS	2.6 (66)	1.4 (35.6)
7-16 DIN Male	OnePiece	<b>L4PDM-RPC</b>	Captivated	Self-Flare	SS	3.1 (78.2)	1.41 (35.9)
7-16 DIN Male	Right Angle	<b>L4PDR</b>	Solder	Self-Flare	SS	1.8/2.8 (46/72)	1.41 (35.9)
7-16 DIN Male	Right Angle	<b>L4PDR-C</b>	Captivated	Self-Flare	SS	1.8/2.8 (46/72)	1.41 (35.9)
7-16 DIN Male	RingFlare	<b>L4PDM-RC</b>	Captivated	Ring-Flare	SS	2.64 (67.1)	0.86 (21.8)
7-16 DIN Female	–	<b>L4PDF</b>	Solder	Self-Flare	SS	2.7 (69)	1.1 (27.9)
7-16 DIN Female	Bulk Head	<b>L4PDF-BH</b>	Solder	Self-Flare	SS	2.73 (69.4)	1.62 (41.1)
7-16 DIN Female	Bulk Head	<b>L4PDF-BHC</b>	Captivated	Self-Flare	SS	2.9 (74)	1.63 (41.4)
7-16 DIN Female	Panel Mount	<b>L4PDF-PM</b>	Solder	Self-Flare	SS	2.7 (69)	1.2 (29.4)
7-16 DIN Female	RingFlare	<b>L4PDF-RC</b>	Captivated	RingFlare	SS	2.8 (71)	0.86 (21.8)
7/8" EIA Flange	–	<b>L44R</b>	Solder	Self-Flare	BB	3.2 (81)	2.25 (57.2)
7/8" EIA Flange	Right Angle	<b>124990-1</b>	Solder	Self-Flare	BB	2.3/1.6 (58/41)	2.25 (57.2)
F Flange Male	–	<b>L44F</b>	Solder	Self-Flare	BB	2.3 (58)	2.25 (57.2)
F Flange Female	–	<b>209865</b>	Solder	Self-Flare	BS	2.3 (58)	2.25 (57.2)
UHF Male	–	<b>L44P</b>	Solder	Self-Flare	BB	2.3 (58)	0.91 (23.1)
UHF Female	–	<b>L44U</b>	Solder	Self-Flare	BS	2.3 (58)	0.91 (23.1)
HN Male	–	<b>L44J</b>	Solder	Self-Flare	BB	2.5 (64)	0.91 (23.1)
LC Male	–	<b>L44M</b>	Solder	Self-Flare	BB	3.6 (91)	0.91 (23.1)
TNC Female	–	<b>L44NT</b>	Solder	Self-Flare	BB	2.8 (71)	0.94 (23.9)
End Terminal	–	<b>L44T</b>	Solder	Self-Flare	BB	4.0 (102)	0.91 (23.1)
Splice	–	<b>L44Z</b>	Solder	Self-Flare	BB	3.2 (81)	1.1 (27.9)

**Plating Codes:** BB - Brass Body and Pin, BS - Brass Body and Silver Plated Pin, SG - Silver Plated Body and Gold Plated Pin, SS - Silver Plated Body and Pin

**Connector Accessories** – See page 624

**Factory Attached Connectors** – For factory made cable assemblies and jumper cables, see pages 584-587.