

# Mini Speakers • Communications Speakers

www.specotech.com • 1-800-645-5516

## ECONOMICAL COMMUNICATION EXTENSION SPEAKER



- Compact size
- Mounting bracket with hardware
- 10 foot cable with 3.5mm mini plug
- 2.7"L x 4.5"W x 4.5"H • 4" • 8 Ohm
- 5 Watt

**CBS-200**

## PROFESSIONAL COMMUNICATION SPEAKER PERFECT FOR CELL PHONES



- Includes bracket with magnet
- 7' cord with mini plug • 8 Ohm
- 5 Watt • 1.25"L x 3"W 2.75"H

**CBS-100**

| 1" TO 5" MINI SPEAKERS                                    |            |                |         |                    |                      |           |                 |                    |
|---|------------|----------------|---------|--------------------|----------------------|-----------|-----------------|--------------------|
| Available in bulk only - 50 piece standard bulk pack Qty. |            |                |         |                    |                      |           |                 |                    |
| MODEL NO.   |            | DIA INCH       | IMP OHM | RESONANT FREQ (Hz) | FREQUENCY RANGE (Hz) | SENSIT dB | POWER NOM WATTS | ALINCO MAG WHT OZ. |
| U101X   | MYLAR CONE | 1" RD          | 8       | 430-530            | FO-5,000             | 89.0      | 0.15            | 0.20               |
| U105X   |            | 1 1/2" RD      | 8       | 430-530            | FO-7,000             | 89.0      | 0.2             | 0.24               |
| U105SX  |            | 1 1/2" SQ      | 8       | 430-530            | FO-7,000             | 89.0      | 0.2             | 0.24               |
| U260X   |            | 2" RD          | 8       | 375-485            | FO-4,500             | 92.0      | 0.2             | 0.33               |
| U260SX  |            | 2" SQ          | 8       | 375-485            | FO-4,500             | 92.0      | 0.2             | 0.33               |
| U261X   |            | 2 1/4" RD      | 8       | 350-450            | FO-5,000             | 93.5      | 0.2             | 0.42               |
| U261SX  | PAPER CONE | 2 1/4" SQ      | 8       | 350-450            | FO-5,000             | 93.5      | 0.2             | 0.42               |
| U265X   |            | 2 1/2" RD      | 8       | 300-400            | FO-5,000             | 94.0      | 0.2             | 0.42               |
| U265SX  |            | 2 1/2" SQ      | 8       | 300-400            | FO-5,000             | 94.0      | 0.2             | 0.42               |
| U208X   |            | 2 3/4" RD      | 8       | 260-340            | FO-4,000             | 95.0      | 0.3             | 0.42               |
| U300X   |            | 3" RD          | 8       | 220-280            | FO-5,000             | 94.5      | 0.5             | 0.42               |
| U300SX  |            | 3" SQ          | 8       | 220-280            | FO-5,000             | 94.5      | 0.5             | 0.42               |
| R305X   |            | 3 1/2" RD      | 8       | 210-260            | FO-5,000             | 94.5      | 0.5             | 0.42               |
| S305X   |            | 3 1/2" SQ      | 8       | 210-260            | FO-5,000             | 94.5      | 0.5             | 0.42               |
| G4AF1X  |            | 4" SQ          | 8       | 210-260            | FO-5,000             | 94.5      | 3.0             | 1.00               |
| G4CA10X   |            | 4" Pin Cushion | 8       | 430-530            | FO-5,000             | 89        | .15             | 10 *               |
| G23AF.5X  |            | 2" x 3" SQ     | 8       | 430-530            | FO-5,000             | 89        | .15             | .57                |
| A4CF3X  |            | 4" SQ          | 8       | 430-530            | FO-5,000             | 89        | .15             | 3 *                |
| A5CF3X  |            | 5" Pin Cushion | 8       | 430-530            | FO-5,000             | 89        | .15             | 3 *                |
| SQ-SQUARE   |            | RD-ROUND       |         |                    |                      |           |                 | *CERAMIC MAGNET    |



## 10W AMPLIFIED DELUXE PROFESSIONAL COMMUNICATIONS EXTENSION SPEAKER

- Swivel bracket for all angles • ABS plastic enclosure • Voltage 12V DC Input
- Impedance 4-8 Ohm • 10W amplified power • 4" - 10W speaker and soft padded grille
- Complete with 10 ft. cord & standard 3.5mm mini plug • 2.5"L x 5.5"W x 4.5"H

**AES-4**



## DELUXE PROFESSIONAL COMMUNICATIONS EXTENSION SPEAKER

- Swivel bracket for all angles • ABS plastic enclosure • Soft padded grille
- Complete with 10 ft. cord with standard 3.5mm mini plug • Controlled speech frequency response (700 - 2 kHz) automatically limits background noise • 4 - 8 Ohms, 10W speaker
- Size 4.5"H x 5.5"W x 2.5"D

**CBS-4**



## ALL WEATHER PROFESSIONAL COMMUNICATIONS EXTENSION SPEAKER

- 5 Watt • Speaker 4" polypropylene • Max. power 5W • Impedance 8 Ohm
- Weatherproof professional marine communications extension speaker with polypropylene cone
- ABS plastic case w/stainless steel hardware and 180° deluxe adjustable mounting bracket
- Prewired 10 ft. cable and 3.5mm miniature plug

White **CBS-240W** Black **CBS-240**